

MKP383430025JF02W0

MKP383430025JF02W0 Information

Heisener.com	MKP383430025JF02W0 Vishay BC Components Capacitors Film Capacitors CAP FILM 0.3UF 5% 250VDC RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP383430025JF02W0 Specifications

Manufacturer Part Number MKP383430025JF02W0 Manufacturer Vishay BC Components Category Capacitors Film Capacitors Film Capacitors Package Radial Series MMKP383 Capacitance 0.3µF Tolerance ±5% Voltage Rating - AC 250V Voltage Rating - DC 250V Dielectric Material Polyropylene (PP), Metallized SPR (Equivalent Series Resistance) - Orduning Type 55°C ~ 105°C Mouting Type Radial Size / Dimension 0.689° L x 0.335° W (17.50mm x 8.50mm) Height - Seated (Max) 0.591" (15.00mm) Lead Spacing 6General Purpose Lead Spacing Size / 115.00mm)		
Category Capacitors Film Capacitors Package Radial Series MMKP383 Capacitance 0.3µF Tolerance ±5% Voltage Rating - AC 125V Voltage Rating - DC 250V Dielectric Material 0.9µpropylene (PP), Metallized Portug Temperature - Operating Type 55°C ~ 105°C Mounting Type Scoll Package / Case Radial Size / Dimension 0.689" L x 0.335" W (17.50mm x 8.50mm) Height - Seated (Max) 0.591" (15.00mm) Lead Spacing 0.591" (15.00mm) Applications General Purpose Features -	Manufacturer Part Number	MKP383430025JF02W0
Fin CapacitorsPackageRadialSeriesMMKP383Capacitance0.3µFTolerance±5%Voltage Rating - AC125VVoltage Rating - DC250VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationGeneral PurposeApplicationsGeneral PurposeFeatures-	Manufacturer	Vishay BC Components
PackageRadialSeriesMMKP383Capacitance0.3µFTolerance±5%Voltage Rating - AC125VVoltage Rating - DC250VDielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HoleSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)Lead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Category	Capacitors
SeriesMMKP383Capacitance0.3µFTolerance±5%Voltage Rating - AC125VVoltage Rating - DC250VDielectric MaterialPolyproplene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.689° L x 0.335° W (17.50mm x 8.50mm)Height - Seated (Max)0.591° (15.00mm)Lead Spacing0.591° (15.00mm)ApplicationsGeneral PurposeFeatures-		Film Capacitors
Capacitance0.3µFTolerance±5%Voltage Rating - AC125VVoltage Rating - DC250VDielectric MaterialPolyproylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 105°CMounting TypeRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsApplications0.591" (15.00mm)Applications0.591" (15.00mm)Features-Features-Features-Features-Features-Features-Features-Features-Features-Features-Features-Features-	Package	Radial
Tolerance±5%Voltage Rating - AC125VVoltage Rating - DC250VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Series	MMKP383
Voltage Rating - AC125VVoltage Rating - DC250VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Capacitance	0.3µF
Voltage Rating - DC250VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	125V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	250V
Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 105°C
Size / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.689" L x 0.335" W (17.50mm x 8.50mm)
Lead Spacing0.591" (15.00mm)ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.591" (15.00mm)
ApplicationsGeneral PurposeFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.591" (15.00mm)
	Applications	General Purpose
Report errors?	Features	-
		Report errors?

MKP383430025JF02W0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MKP383430025JF02W0 Payment Methods



If you have any question about MKP383430025JF02W0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com