

MKP385218085JCM2B0

MKP385218085JCM2B0 Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP385218085JCM2B0 Specifications

ManufacturerVishay BC ComponentsCapacitorsCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesMKP385Capacitance1800pFTolerance±5%Voltage Rating - DC300VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-5°C ~ 110°CPackage / CaseRadialSize / Dimension0.315" (8.00mm)Height - Seated (Max)0.315" (8.00mm)FerminationCP insLead Spacing.029S" (7.50mm)Features.Features.		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesMKP385Capacitance1800pFColerance±5%Voltage Rating - AC300VSolve850VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 110°CPackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)PerminationPC PinsLead Spacing0.295" (7.50mm)Applications-Features-	Manufacturer Part Number	MKP385218085JCM2B0
Film CapacitorsPackageRadialPackageMKP385Capacitance1800pFTolerance±5%Voltage Rating - AC300VVoltage Rating - DC850VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)PerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components
PackageRadialSeriesMKP385Capacitance1800pFTolerance±5%Voltage Rating - AC300VVoltage Rating - DC850VDielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Fermination0.295" (7.50mm)Lead Spacing0.295" (7.50mm)Features-Features-	Category	Capacitors
Series MKP385 Capacitance 1800pF Folerance ±5% Voltage Rating - AC 300V Voltage Rating - DC 850V Dielectric Material Polypropylene (PP), Metallized Dielectric Material olypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.315" (8.00mm) Height - Seated (Max) 0.315" (8.00mm) Lead Spacing 0.295" (7.50mm) Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -		Film Capacitors
Capacitance1800pFTolerance±5%Voltage Rating - AC300VVoltage Rating - DC850VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material-ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)FerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package	Radial
Folerance±5%Voltage Rating - AC300VVoltage Rating - DC850VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)PerminationPC PinsLead Spacing0.295" (7.50mm)Applications-Features-	Series	MKP385
Voltage Rating - AC300VVoltage Rating - DC850VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)FerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	1800pF
Voltage Rating - DC850VDelectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)PerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	±5%
Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)FerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	300V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)PerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	850V
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)FerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialPackage / Case0.394" L x 0.118" W (10.00mm x 3.00mm)Size / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)FerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)FerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 110°C
Size / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.315" (8.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	0.394" L x 0.118" W (10.00mm x 3.00mm)
Lead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	0.315" (8.00mm)
Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -	Termination	PC Pins
Features -	Lead Spacing	0.295" (7.50mm)
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT
Report errors?	Features	-
		Report errors?

MKP385218085JCM2B0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MKP385218085JCM2B0 Payment Methods





If you have any question about MKP385218085JCM2B0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com