

MKP385243063JC02W0

MKP385243063JC02W0 Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP385243063JC02W0 Specifications

ManufacturerVishay BC ComponentsCapacitorsCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesMKP385Capacitance4300pFColerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedDiperating Temperature-Operating Temperature-5°C ~ 110°CPackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Eight - Seated (Max)0.315" (8.00mm)FerminationPC PinsCadaSpacing.0295" (7.50mm)Features-Features-		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesMKP385Capacitance4300pFColerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 110°CVoltage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)FerminationPC PinsLead Spacing0.295" (7.50mm)Applications-Features-	Manufacturer Part Number	MKP385243063JC02W0
Film CapacitorsPackageRadialSeriesMKP385Capacitance4300pFTolerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)PerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components
PackageRadiaSeriesMKP385Capacitance4300pFTolerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CVoltage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Fermination0.315" (8.00mm)Fermination0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors
Series MKP385 Capacitance 4300pF Folerance ±5% Voltage Rating - AC 220V Voltage Rating - DC 630V Dielectric Material Polypropylene (PP), Metallized Dielectric Material 01/9 ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.394" L x 0.118" W (10.00mm x 3.00mm) Height - Seated (Max) 0.315" (8.00mm) Fermination PC Pins Lead Spacing 0.295" (7.50mm) Applications JC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -		Film Capacitors
Capacitance4300pFTolerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material-ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)FerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC L Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package	Radial
Folerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)PerminationPC PinsLead Spacing0.295" (7.50mm)Applications-Features-	Series	MKP385
Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)FerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	4300pF
Voltage Rating - DC630VDelectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)PerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)FerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	220V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)FerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	630V
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialPackage / Case0.394" L x 0.118" W (10.00mm x 3.00mm)Size / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)FerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Mounting TypeThrough HolePackage / CaseRadialPackage / Case0.394" L x 0.118" W (10.00mm x 3.00mm)Size / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)FerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)FerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 110°C
Size / Dimension0.394" L x 0.118" W (10.00mm x 3.00mm)Height - Seated (Max)0.315" (8.00mm)FerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.315" (8.00mm)FerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	0.394" L x 0.118" W (10.00mm x 3.00mm)
Lead Spacing0.295" (7.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	0.315" (8.00mm)
ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.295" (7.50mm)
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT
Report errors?	Features	-
1		Report errors?

MKP385243063JC02W0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

MKP385243063JC02W0 Payment Methods



MKP385243063JC02W0 Shipping Methods



If you have any question about MKP385243063JC02W0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com