

MKP385282200JFI2B0

MKP385282200JFI2B0 Information

Heisener.com	Part Number	MKP385282200JFI2B0	
	Manufacturer	Vishay BC Components	
	Category	Capacitors Film Capacitors	
	Description	CAP FILM 8200PF 5% 2KVDC RADIAL	- 29
	Package	Radial	一部
		For the pricing/inventory/lead time, please contact	
For Reference Only		us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Requ

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



est a Quote

MKP385282200JFI2B0 Specifications

Manufacturer Part Number MKP385282200JF12B0 Manufacturer Vishay BC Components Category Capacitors Film Capacitors Film Capacitors Package Radial Series MKP385 Capacitance 8200pF Tolerance ±5% Voltage Rating - AC 700V Voltage Rating - DC 2000V (2kV) Dielectric Material Polypropylene (PP), Metallized Sprogen Hammed Mathematica - Operating Temperature - Operating Temperature - Size / Dimension 6.689" L x 0.276" W (17.50mm x 7.00mm) Height - Seated (Max) 0.532" (13.50mm) Lead Spacing 0.591" (15.00mm) Applications 0.591" (15.00mm)	_		
Category Capacitors Film Capacitors Film Capacitors Package Radial Series MKP385 Capacitance 8200pF Tolerance ±5% Voltage Rating - AC 700V Voltage Rating - DC 2000V (2kV) Dielectric Material Polypropylene (PP), Metallized Operating Temperature - Operating Type Through Hole Nounting Type Sciel Number (11.50mm x 7.00mm) Size / Dimension 0.689" L x 0.276" W (17.50mm x 7.00mm) Height - Seated (Max) 0.532" (13.50mm) Lead Spacing 0.591" (15.00mm) Applications DSci Init, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -	Manufacturer Part Number	MKP385282200JFI2B0	
Fin CapacitorsPackageRadialSeriesMKP385Capacitance8200pFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689° L x 0.276° W (17.50mm x 7.00mm)Height - Seated (Max)0.532° (13.50mm)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components	
PackageRadiaSeriesMKP385Capacitance8200pFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689° L x 0.276° W (17.50mm x 7.00mm)Height - Seated (Max)0.532° (13.50mm)Perination0.591° I (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors	
Series MKP385 Capacitance 8200pF Tolerance 5% Voltage Rating - AC 700V Voltage Rating - DC 2000V (2kV) Dielectric Material Polypropylene (PP), Metallized DSR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.632" (13.50mm) X .00mm) Height - Seated (Max) 0.531" (15.00mm) Lead Spacing 0.591" (15.00mm) Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -		Film Capacitors	
Capacitance8200pFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package	Radial	
Tolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)Applications0.591" (15.00mm)Features-	Series	MKP385	
Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	8200pF	
Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	$\pm 5\%$	
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	700V	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	2000V (2kV)	
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized	
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-	
Package / CaseRadialSize / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 110°C	
Size / Dimension0.689" L x 0.276" W (17.50mm x 7.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole	
Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial	
TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	0.689" L x 0.276" W (17.50mm x 7.00mm)	
Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	0.532" (13.50mm)	
ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Termination	PC Pins	
Features -	Lead Spacing	0.591" (15.00mm)	
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	
Report errors?	Features	-	
1		Report errors?	

MKP385282200JFI2B0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MKP385282200JFI2B0 Payment Methods





If you have any question about MKP385282200JFI2B0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com