

MKP385291160JFI2B0

MKP385291160JFI2B0 Information

Heisener.com	Part Number Manufacturer Category Description Package	MKP385291160JFI2B0 Vishay BC Components Capacitors Film Capacitors CAP FILM 9100PF 5% 1.6KVDC RAD Radial For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP385291160JFI2B0 Specifications

Manufacturer Part NumberMKP385291160JF12B0ManufacturerVishay BC ComponentsCategoryCapacitorsFiln CapacitorsFiln CapacitorsPackageRadialSeriesMKP385Capacitance9100pFTolerance±5%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolyproylene (PP), MetallizedOperating Temperature-Voltage Rating - Series-Monting Type55°C ~ 110°CMonting TypeRadialSize / Dimension0.689° L x 0.197° W (17.50mm x 5.00mm)Field Stacting0.433° (11.00mm)Fiendiation9.051° (15.00mm)Leid Spacing0.591° (15.00mm)KapleationsD.610° (16.00mm)KapleationsD.610° (16.00mm) <th>_</th> <th></th>	_		
CategoryCapacitorsPackageRadialPackageRadialSeriesMKP385Capacitance9100pFTolerance55%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 110°CMounting TypeThrough HoleSize / Dimension0.689° L x 0.197° W (17.50mm x 5.00mm)Height - Seated (Max)0.591° (15.00mm)Lead Spacing0.591° (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Manufacturer Part Number	MKP385291160JFI2B0	
Film CapacitorsPackageRadialSeriesMKP385Capacitance9100pFTolerance±5%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HoleSize / Dimension0.689° L x 0.197° W (17.50mm x 5.00mm)Height - Seated (Max)0.433° (11.00mm)TerminationPC PinsLead Spacing0.591° (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Manufacturer	Vishay BC Components	
PackageRadiaSeriesMKP385Capacitance9100pFTolerance±5%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolyproplene (PP), MetallizedDielectric Material-Operating Temperature-55° < 110°C	Category	Capacitors	
Series MKP385 Capacitance 9100pF Tolerance 55% Voltage Rating - AC 550V Voltage Rating - DC 1600V (1.6kV) Dielectric Material Polypropylene (PP), Metallized Dielectric Material - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.689" L x 0.197" W (17.50mm x 5.00mm) Height - Seated (Max) 0.433" (11.00mm) Lead Spacing 0.591" (15.00mm) Applications Dicy Filtering; High Frequency, Switching; High Pulse, DV/DT		Film Capacitors	
Capacitance9100pFTolerance±5%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolyproplene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689° L x 0.197° W (17.50mm x 5.00mm)Height - Seated (Max)0.433° (11.00mm)TerminationDC PinsApplications0.591° (15.00mm)Dielectric MaterialDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Package	Radial	
Tolerance±5%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Series	MKP385	
Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Capacitance	9100pF	
Voltage Rating - DC1600V (1.6kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Tolerance	±5%	
Dielectric MaterialPolypropylene (PP), MetallizedDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Voltage Rating - AC	550V	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Voltage Rating - DC	1600V (1.6kV)	
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Dielectric Material	Polypropylene (PP), Metallized	
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	ESR (Equivalent Series Resistance)	-	
Package / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Operating Temperature	-55°C ~ 110°C	
Size / Dimension 0.689" L x 0.197" W (17.50mm x 5.00mm) Height - Seated (Max) 0.433" (11.00mm) Termination PC Pins Lead Spacing 0.591" (15.00mm) Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Mounting Type	Through Hole	
Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Package / Case	Radial	
TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Size / Dimension	0.689" L x 0.197" W (17.50mm x 5.00mm)	
Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Height - Seated (Max)	0.433" (11.00mm)	
Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Termination	PC Pins	
	Lead Spacing	0.591" (15.00mm)	
	Applications	ications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	
reatures -	Features	-	
Report errors?		Report errors?	

MKP385291160JFI2B0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

MKP385291160JFI2B0 Payment Methods



MKP385291160JFI2B0 Shipping Methods



If you have any question about MKP385291160JFI2B0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com