

MKP385311250JIP2T0

MKP385311250JIP2T0 Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP385311250JIP2T0 Specifications

ManufacturerVishay BC ComponentsCategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesMKP385Capacitance0.011µFFolerance±5%Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolyproplene (PP), MetallizedDeperating Temperature-Operating Temperature-55°C ~ 110°CPackage / CaseRadialSize / Dimension1.024" L x 0.335" W (26.00mm x 8.50mm)Height - Seated (Max)0.708" (18.00mm)FerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT		
CategoryCapacitorsPackageRadialPackageMKP385Capacitance0.011µFColarance±5%Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolypropylene (PP), MetallizedCoperating Temperature-Capacitage / CaseRadialSize / Dimension1.024" L x 0.335" W (26.00mm x 8.50mm)Height - Seated (Max)0.708" (18.00mm)FerminationPC PinsCapacitage0.886" (22.50mm)Capacitage0.886" (22.50mm)Capacitage / Case0.010000000000000000000000000000000000	Manufacturer Part Number	MKP385311250JIP2T0
Fin CapacitorsPackageRadialSeriesMKP385Capacitance0.011µFTolerance±5%Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.335" W (26.00mm x 8.50mm)Height - Seated (Max)0.708" (18.00mm)Per Pins0.886" (22.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components
PackageRadialPackageRadialSeriesMKP385Capacitance0.011µFFolerance±5%Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.335" W (26.00mm x 8.50mm)Fermination0.708" (18.00mm)Evad Spacing0.886" (22.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors
Series MKP385 Capacitance 0.011µF Folerance ±5% Voltage Rating - AC 900V Voltage Rating - DC 2500V (2.5kV) Dielectric Material Polypropylene (PP), Metallized Dielectric Material - Diperating Temperature -55°C ~ 110°C Package / Case Radial Size / Dimension 1.024" L x 0.335" W (26.00mm x 8.50mm) Height - Seated (Max) 0.708" (18.00mm) Fermination PC Pins Applications 0.886" (22.50mm) Applications - Features -		Film Capacitors
Capacitance0.011μFColarace±5%Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolyproylene (PP), MetallizedDielectric Material-ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.708" (18.00mm) x 8.50mm)Height - Seated (Max)0.708" (18.00mm)PerminationPC PinsLead Spacing0.886" (22.50mm)Applications-Features-	Package	Radial
Tolerance±5%Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Delectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.335" W (26.00mm x 8.50mm)Height - Seated (Max)0.708" (18.00mm)PerminationPC PinsLead Spacing0.886" (22.50mm)Applications-Features-	Series	MKP385
Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.335" W (26.00mm x 8.50mm)Height - Seated (Max)0.708" (18.00mm)FerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	0.011µF
Voltage Rating - DC2500V (2.5kV)Delectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.335" W (26.00mm x 8.50mm)Height - Seated (Max)0.708" (18.00mm)PerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.335" W (26.00mm x 8.50mm)Height - Seated (Max)0.708" (18.00mm)FerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	900V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.335" W (26.00mm x 8.50mm)Height - Seated (Max)0.708" (18.00mm)FerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	2500V (2.5kV)
Derating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.335" W (26.00mm x 8.50mm)Height - Seated (Max)0.708" (18.00mm)FerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Noncing TypeThrough HolePackage / CaseRadialPackage / Case1.024" L x 0.335" W (26.00mm x 8.50mm)Beight - Seated (Max)0.708" (18.00mm)FerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension1.024" L x 0.335" W (26.00mm x 8.50mm)Height - Seated (Max)0.708" (18.00mm)FerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	$-55^{\circ}C \sim 110^{\circ}C$
Size / Dimension1.024" L x 0.335" W (26.00mm x 8.50mm)Height - Seated (Max)0.708" (18.00mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.708" (18.00mm)FerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	1.024" L x 0.335" W (26.00mm x 8.50mm)
Lead Spacing0.886" (22.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	0.708" (18.00mm)
Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -	Termination	PC Pins
Features -	Lead Spacing	0.886" (22.50mm)
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT
Report errors?	Features	-
		Report errors?

MKP385311250JIP2T0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MKP385311250JIP2T0 Payment Methods





If you have any question about MKP385311250JIP2T0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com