

# MKP385313160JC02Z0

#### MKP385313160JC02Z0 Information

Heisener.com	 MKP385313160JC02Z0 Vishay BC Components Capacitors Film Capacitors CAP FILM 0.013UF 5% 1.6KVDC RAD Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## MKP385313160JC02Z0 Specifications

Manufacturer Part NumberMKP385313160/C02Z0ManufacturerVishay BC ComponentsCategoryCapacitorsPackageFilm CapacitorsPackageRadialSeriesMKP385Capacitance0.013µFTolerance±5%Voltage Rating - AC50VVoltage Rating - DC1600V (1.6kV)Dielectric Material-Porpolyenc (PP), MetallizedMounting Type-Package / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seaded (Max)0.550" (14.00mm)
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesMKP385Capacitance0.013µFTolerance±5%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric Material>140yropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.550" (14.00mm)
Film CapacitorsPackageRadialSeriesMKP385Capacitance0.013μFTolerance±5%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.550" (14.00mm)
PackageRadialPackageMKP385Capacitance0.013µFTolerance±5%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.550" (14.00mm)
SeriesMKP385Capacitance0.013µFTolerance±5%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.550" (14.00mm)
Capacitance0.013µFTolerance±5%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.550" (14.00mm)
Tolerance±5%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.550" (14.00mm)
Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.550" (14.00mm)
Voltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.550" (14.00mm)
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.550" (14.00mm)
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.550" (14.00mm)
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.550" (14.00mm)
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.236" W (17.50mm x 6.00mm)Height - Seated (Max)0.550" (14.00mm)
Package / Case Radial   Size / Dimension 0.689" L x 0.236" W (17.50mm x 6.00mm)   Height - Seated (Max) 0.550" (14.00mm)
Size / Dimension 0.689" L x 0.236" W (17.50mm x 6.00mm)   Height - Seated (Max) 0.550" (14.00mm)
Height - Seated (Max) 0.550" (14.00mm)
• · · · · · · · · · · · · · · · · · · ·
Termination PC Pins
Lead Spacing 0.295" (7.50mm)
Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT
Features -
Report error

#### MKP385313160JC02Z0 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

#### MKP385313160JC02Z0 Payment Methods



### MKP385313160JC02Z0 Shipping Methods



If you have any question about MKP385313160JC02Z0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com