

MKP385316200JFI2B0

MKP385316200JFI2B0 Information

Heisener.com	Part Number Manufacturer Category Description Package		
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP385316200JFI2B0 Specifications

Manufacturer Part NumberMKP385316200JFI2B0ManufacturerVishay BC ComponentsCategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesMKP385Capacitance0.016µFTolerance±5%Voltage Rating - AC00VVoltage Rating - DC200V (2kV)Dielectric MaterialPolypropelne (PP), MetallizedSeries55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSiz/ Dimension0.689° L x 0.335° W (17.50mm x 8.50mm)Height - Seated (Max)0.591° (15.00mm)Lead Spacing0.591° (15.00mm)Lead Spacing0.591° (15.00mm)ApplicationsSD1° (15.00mm)Features-			
CategoryCaracitorsFilm CapacitorsPackageRadialPackageMKP385Capacitance0.016µFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-5°C ~ 110°CMounting TypeThrough HoleSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Manufacturer Part Number	MKP385316200JFI2B0	
Film CapacitorsPackageRadialSeriesMKP385Capacitance0.016µFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HoleSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Manufacturer	Vishay BC Components	
PackageRadiaSeriesMKP385Capacitance0.016µFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedDiegerating Temperature-Operating Temperature-5°C ~ 110°CMunting TypeRadiaSize / Dimension689° L x 0.335° W (17.50mm x 8.50mm)Height - Seated (Max)0.591° (15.00mm)FerminationDC PinsApplications0.591° (15.00mm)Applications0.591° (15.00mm)	Category	Capacitors	
Yeires MKP385 Capacitance 0.016µF Tolerance ±5% Voltage Rating - AC 700V Voltage Rating - DC 2000V (2kV) Dielectric Material Polypropylene (PP), Metallized Poperating Temperature - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.689" L x 0.335" W (17.50mm x 8.50mm) Height - Seated (Max) 0.591" (15.00mm) Performation DC Pins Lead Spacing 0.591" (15.00mm) Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT		Film Capacitors	
Capacitance0.016µFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Package	Radial	
Tolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.589" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Series	MKP385	
Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Capacitance	0.016µF	
Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Tolerance	$\pm 5\%$	
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Voltage Rating - AC	700V	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Voltage Rating - DC	2000V (2kV)	
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Dielectric Material	Polypropylene (PP), Metallized	
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	ESR (Equivalent Series Resistance)	-	
Package / CaseRadialSize / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Operating Temperature	-55°C ~ 110°C	
Size / Dimension0.689" L x 0.335" W (17.50mm x 8.50mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Mounting Type	Through Hole	
Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Package / Case	Radial	
TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Size / Dimension	0.689" L x 0.335" W (17.50mm x 8.50mm)	
Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Height - Seated (Max)	0.591" (15.00mm)	
Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Termination	PC Pins	
	Lead Spacing	0.591" (15.00mm)	
Features -	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	
	Features	-	
Report errors?		Report errors?	

MKP385316200JFI2B0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MKP385316200JFI2B0 Payment Methods





If you have any question about MKP385316200JFI2B0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com