

MKP385322040JD02W0

MKP385322040JD02W0 Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP385322040JD02W0 Specifications

ManufacturerVishay BC ComponentsCapacitorsCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesMKP385Capacitance0.022µFTolerance±5%Voltage Rating - DC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedCoperating Temperature-Operating Temperature-5°C ~ 110°CPackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)ParinationC PinsLead Spacing0.394" (10.00mm)Applications0.394" (10.00mm)Kapilications0.394" (10.00mm)Kapilications0.394" (10.00mm)Applications0.294" L x 0.158" Kirk in graduent, witching; High Pulse, DV/DTFeatures-		
CategoryCapacitorsCapacitorsFilm CapacitorsPackageRadialSeriesMKP385Capacitance0.022µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492° L x 0.158° W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)ParinationPC PinsLead Spacing0.394" (10.00mm)Applications0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer Part Number	MKP385322040JD02W0
Film CapacitorsPackageRadialSeriesMKP385Capacitance0.022µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492° L x 0.158° W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)PC Pins0.394" (10.00mm)ApplicationsDC L Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components
PackageRadialSeriesMKP385Capacitance0.022µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)PerminationC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors
Series MKP385 Capacitance 0.022µF Tolerance ±5% Voltage Rating - AC 200V Voltage Rating - DC 400V Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.492" L x 0.158" W (12.50mm x 4.00mm) Height - Seated (Max) 0.394" (10.00mm) Lead Spacing 0.394" (10.00mm) Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -		Film Capacitors
Capacitance0.022µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package	Radial
Tolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Series	MKP385
Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	0.022µF
Voltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	200V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	400V
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 110°C
Size / Dimension0.492" L x 0.158" W (12.50mm x 4.00mm)Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.394" (10.00mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	0.492" L x 0.158" W (12.50mm x 4.00mm)
Lead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	0.394" (10.00mm)
Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -	Termination	PC Pins
Features -	Lead Spacing	0.394" (10.00mm)
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT
Report errors?	Features	-
		Report errors?

MKP385322040JD02W0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MKP385322040JD02W0 Payment Methods





If you have any question about MKP385322040JD02W0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com