

MKP385322200JFI2B0

MKP385322200JFI2B0 Information

Heisener.com	Part Number Manufacturer Category Description Package		
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP385322200JFI2B0 Specifications

Manufacturer Part Number MKP385322200JFI2B0 Manufacturer Vishay BC Components Category Capacitors Film Capacitors Film Capacitors Package Radial Series MKP385 Capacitance 0.022µF Tolerance ±5% Voltage Rating - AC 700V Voltage Rating - DC 2000V (2kV) Dielectric Material Polypropylene (PP), Metallized Sproge Package - Operating Temperature - Operating Type Through Hole Size / Dimension 0.650" (16.50mm) Height - Seated (Max) 0.50" (16.50mm) Lead Spacing 0.591" (15.00mm) Applications Displications; High Frequency, Switching; High Pulse, DV/DT Features -	_	
Category Capacitors Film Capacitors Film Capacitors Package Radial Series MKP385 Capacitance 0.022µF Tolerance ±5% Voltage Rating - AC 700V Voltage Rating - DC 2000V (2kV) Dielectric Material Polypropylene (PP), Metallized Operating Temperature - Operating Type Through Hole Nounting Type Cagoit (6.50mm) Size / Dimension 0.689" L x 0.394" W (17.50mm x 10.00mm) Height - Seated (Max) 0.650" (16.50mm) Lead Spacing 0.591" (15.00mm) Applications DS1" (15.00mm) Applications Calout CF Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Manufacturer Part Number	MKP385322200JFI2B0
Fin CapacitorsPackageRadialSeriesMKP385Capacitance0.022µFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689° L x 0.394° W (17.50mm x 10.00mm)Height - Seated (Max)0.650° (16.50mm)Lead Spacing0.591° (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components
PackageRadiaSeriesMKP385Capacitance0.022µFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.650° (16.50mm) 10.00mm)Height - Seated (Max)0.591° (15.00mm)Applications0.591° (15.00mm)Applications	Category	Capacitors
Series MKP385 Capacitance 0.022µF Tolerance 5% Voltage Rating - AC 700V Voltage Rating - DC 000V (2kV) Dielectric Material Polypropylene (PP), Metallized Dielectric Material - Operating Temperature - Mounting Type - Package / Case Radial Size / Dimension 0.650" (16.50mm) x 10.00mm) Termination CPins Lead Spacing 0.591" (15.00mm) Applications Discliciting; High Frequency, Switching; High Pulse, DV/DT Features -		Film Capacitors
Capacitance0.022µFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package	Radial
Tolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.650" (16.50mm x 10.00mm)Height - Seated (Max)0.551" (15.00mm)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Series	MKP385
Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolyproylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)TerminationCP insLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	0.022µF
Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)Termination0.591" (15.00mm)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	700V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	2000V (2kV)
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 110°C
Size / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.650" (16.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	0.689" L x 0.394" W (17.50mm x 10.00mm)
Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	0.650" (16.50mm)
ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.591" (15.00mm)
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT
Report errors?	Features	-
		Report errors?

MKP385322200JFI2B0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

MKP385322200JFI2B0 Payment Methods



MKP385322200JFI2B0 Shipping Methods



If you have any question about MKP385322200JFI2B0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com