

MKP385339063JFI2B0

MKP385339063JFI2B0 Information

Heisener.com	Part Number Manufacturer Category Description Package	MKP385339063JFI2B0 Vishay BC Components Capacitors Film Capacitors CAP FILM 0.039UF 5% 630VDC RAD Radial For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP385339063JFI2B0 Specifications

Manufacturer Part NumberMKP385339063JF12B0ManufacturerVishay BC ComponentsCategoryCapacitorsPackageRadialPackageRadialSeriesMKP385Capacitance0.039µFTolerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolyproplene (PP), MetallizedDoperating Temperature-5°C ~ 110°CMounting TypeFinough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)
CategoryCapacitorsPackageRadialPackageRadialSeriesMKP385Capacitance0.039μFTolerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Type55°C ~ 110°CMounting TypeRadialSize / Dimension0.689° L x 0.197° W (17.50mm x 5.00mm)
Film CapacitorsPackageRadialSeriesMKP385Capacitance0.039µFTolerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)
PackageRadialPackageMKP385Capacitance0.039µFTolerance±5%Voltage Rating - AC20VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197"W (17.50mm x 5.00mm)
Series MKP385 Capacitance 0.039µF Tolerance ±5% Voltage Rating - AC 220V Voltage Rating - DC 630V Dielectric Material Polyropylene (PP), Metallized SSR (Equivalent Series Resistance) - Operating Type 55°C ~ 110°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.689" L x 0.197"W (17.50mm x 5.00mm)
Capacitance0.039µFTolerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedDSR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)
Tolerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)
Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)
Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)
Package / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)
Size / Dimension 0.689" L x 0.197" W (17.50mm x 5.00mm)
Height - Seated (Max) 0.433" (11.00mm)
Termination PC Pins
Lead Spacing 0.591" (15.00mm)
Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT
Features -
Report errors

MKP385339063JFI2B0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

MKP385339063JFI2B0 Payment Methods



MKP385339063JFI2B0 Shipping Methods



If you have any question about MKP385339063JFI2B0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com