

MKP385362040JD02G0

MKP385362040JD02G0 Information

Heisener.com	 MKP385362040JD02G0 Vishay BC Components Capacitors Film Capacitors CAP FILM 0.062UF 5% 400VDC RAD Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP385362040JD02G0 Specifications

Manufacturer Part Number MKP385362040JD02G0 Manufacturer Vishay BC Components Category Capacitors Film Capacitors Film Capacitors Package Radial Series MKP385 Capacitance 0.062µF Tolerance ±5% Voltage Rating - AC 200V Voltage Rating - DC 400V Dielectric Material Polypropylene (PP), Metallized Sprategory -5°C ~ 110°C Mounting Type Strongh Hole Package / Case Radial Size / Dimension 0.453° (11.50mm) Height - Seated (Max) 0.594° (10.00mm) Lead Spacing 0.394° (10.00mm) Lead Spacing CLink, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	_	
Category Capacitors Film Capacitors Film Capacitors Package Radial Series MKP385 Capacitance 0.062µF Tolerance ±5% Voltage Rating - AC 200V Voltage Rating - DC 400V Dielectric Material Polyropylene (PP), Metallized Operating Temperature - Operating Type Through Hole Nounting Type Radial Size / Dimension 0.492" L x 0.197" W (12.50mm x 5.00mm) Height - Seated (Max) 0.394" (10.00mm) Applications DSI-Piltering; High Frequency, Switching; High Pulse, DV/DT Features -	Manufacturer Part Number	MKP385362040JD02G0
Film CapacitorsPackageRadialSeriesMKP385Capacitance0.062µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492° L x 0.197° W (12.50mm x 5.00mm)Height - Seated (Max)0.453° (11.50mm)Perins0.394" (10.00mm)ApplicationsDC L Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components
PackageRadiaSeriesMKP385Capacitance0.062µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeHrough HolePackage / CaseRadialSize / Dimension0.492° L x 0.197° W (12.50mm x 5.00mm)Height - Seated (Max)0.493" (11.50mm)Lead Spacing0.394" (10.00mm)ApplicationsD C Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors
Series MKP385 Capacitance 0.062µF Tolerance ±5% Voltage Rating - AC 200V Voltage Rating - DC 400V Dielectric Material Polypropylene (PP), Metallized Dielectric Material - Dyorating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.492" L x 0.197" W (12.50mm x 5.00mm) Height - Seated (Max) 0.394" (10.00mm) Lead Spacing 0.394" (10.00mm) Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -		Film Capacitors
Capacitance0.062µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.493" (11.50mm)PerminationCP PinsLead Spacing0.394" (10.00mm)ApplicationsSize / Dimension, Size / DimensionApplicationsSize / DimensionLead Spacing0.59C - 110°CApplications0.59C - 110°CCurrent and the provided of the	Package	Radial
Tolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.453" (11.50mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC L Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Series	MKP385
Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolyproylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.453" (11.50mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	0.062µF
Voltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.453" (11.50mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.453" (11.50mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	200V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.453" (11.50mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	400V
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.453" (11.50mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.453" (11.50mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.453" (11.50mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 110°C
Size / Dimension0.492" L x 0.197" W (12.50mm x 5.00mm)Height - Seated (Max)0.453" (11.50mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.453" (11.50mm)TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	0.492" L x 0.197" W (12.50mm x 5.00mm)
Lead Spacing0.394" (10.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	0.453" (11.50mm)
ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.394" (10.00mm)
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT
Report errors?	Features	-
Report crois:		Report errors?

MKP385362040JD02G0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MKP385362040JD02G0 Payment Methods



If you have any question about MKP385362040JD02G0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com