

MKP385416200JKP2T0

MKP385416200JKP2T0 Information

Heisener.com Gistal Write Land Terr	Part Number Manufacturer Category Description Package	MKP385416200JKP2T0 Vishay BC Components Capacitors Film Capacitors CAP FILM 0.16UF 5% 2KVDC RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP385416200JKP2T0 Specifications

SeriesMKP385Capacitance0.16µFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsApplications0.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	_		
Category Capacitors Film Capacitors Film Capacitors Package Radial Series MKP385 Capacitance 0.16µF Tolerance ±5% Voltage Rating - AC 700V Voltage Rating - DC 2000V (2kV) Dielectric Material Polypropylene (PP), Metallized Operating Temperature - Operating Type Through Hole Noutning Type Through Hole Size / Dimension 1.240° L x 0.709° W (31.50mm x 18.00mm) Height - Seated (Max) 1.00° (28.00mm) Termination PC Pins Lead Spacing 1.083° (27.50mm) Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -	Manufacturer Part Number	MKP385416200JKP2T0	
Film CapacitorsPackageRadialSeriesMKP385Capacitance0.16µFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240° L x 0.709° W (31.50mm x 18.00mm)Height - Seated (Max)1.000° (28.00mm)Lead Spacing1.083° (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components	
PackageRadiaSeriesMKP385Capacitance0.16µFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240° L x 0.709° W (31.50mm x 18.00mm)Height - Seated (Max)1.100° (28.00mm)Per IminationPC PinsApplicationsJCL Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors	
Series MKP385 Capacitance 0.16µF Tolerance ±5% Voltage Rating - AC 700V Voltage Rating - DC 2000V (2kV) Dielectric Material Polypropylene (PP), Metallized DSR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.240° L x 0.709° W (31.50mm x 18.00mm) Height - Seated (Max) 1.00° (28.00mm) Termination PC Pins Lead Spacing 1.083° (27.50mm) Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -		Film Capacitors	
Capacitance0.16µFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsSc Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package	Radial	
Tolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)Applications-Features-	Series	MKP385	
Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.00" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	0.16µF	
Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240° L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	$\pm 5\%$	
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	700V	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	2000V (2kV)	
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized	
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-	
Package / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 110°C	
Size / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole	
Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial	
TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	1.240" L x 0.709" W (31.50mm x 18.00mm)	
Lead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	1.100" (28.00mm)	
ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Termination	PC Pins	
Features -	Lead Spacing	1.083" (27.50mm)	
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	
Report errors?	Features	-	
		Report errors?	

MKP385416200JKP2T0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

MKP385416200JKP2T0 Payment Methods



MKP385416200JKP2T0 Shipping Methods



If you have any question about MKP385416200JKP2T0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com