

МКР385420250ЈРМ4Т0

MKP385420250JPM4T0 Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP385420250JPM4T0 Specifications

Manufacturer Vishay BC Components Capacitors Capacitors Package Radial Series MKP385 Capacitors MKP385 Capacitance 0.2µF Folerance ±5% Voltage Rating - AC 900V Voltage Rating - DC 2500V (2.5kV) Dielectric Material Polypropylene (PP), Metallized Opperating Temperature - Opperating Temperature -5°C ~ 110°C Package / Case Radial Size / Dimension 1.693" L x 0.846" W (43.00mm x 21.50mm) Height - Seated (Max) 1.516" (38.50mm) Fermination PC Pins Lead Spacing 1.476" (37.50mm) Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -		
CatagoryCapacitorsFilm CapacitorsPackageRadialSeriesMKP385Capacitance0.2µFFolerance±5%Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 110°CPackage / CaseRadialSize / Dimension1.693° L x 0.846° W (43.00mm x 21.50mm)Height - Seated (Max)1.516° (38.50mm)FerminationPC PinsLead Spacing1.476° (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer Part Number	MKP385420250JPM4T0
Film CapacitorsPackageRadialSeriesMKP385Capacitance0.2µFFolerance±5%Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolypropylene (PP), Metallized2SR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CPolynogh HoleRadialPackage / CaseRadialSize / Dimension1.693° L x 0.846° W (43.00mm x 21.50mm)Height - Seated (Max)1.516° (38.50mm)FerminationPC PinsApplications1.476° (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components
PackageRadialSeriesMKP385Capacitance0.2µFFolerance±5%Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 110°CPougn HoleRadialPackage / CaseRadialSize / Dinension1.516" (38.50mm) x 21.50mm)Height - Seated (Max)1.516" (37.50mm)Cead SpacingDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors
Series MKP385 Capacitance 0.2µF Folerance ±5% Voltage Rating - AC 900V Voltage Rating - DC 2500V (2.5kV) Dielectric Material Polypropylene (PP), Metallized Dielectric Material - Diegrating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.693" L x 0.846" W (43.00mm x 21.50mm) Fermination PC Pins Lead Spacing 1.476" (37.50mm) Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -		Film Capacitors
Capacitance0.2μFFolerance±5%Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-SSR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CPackage / CaseRadialSize / Dimension1.693° L x 0.846° W (43.00mm x 21.50mm)Height - Seated (Max)1.516° (38.50mm)FerminationPC PinsLead Spacing1.476° (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package	Radial
Folerance±5%Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Delectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.693" L x 0.846" W (43.00mm x 21.50mm)Height - Seated (Max)1.516" (38.50mm)PerminationPC PinsLead Spacing1.476" (37.50mm)Applications-Features-	Series	MKP385
Voltage Rating - AC900VVoltage Rating - DC2500V (2.5kV)Delectric MaterialPolypropylene (PP), MetallizedDelectric Material-SSR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.693" L x 0.846" W (43.00mm x 21.50mm)Height - Seated (Max)1.516" (38.50mm)FerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	0.2µF
Voltage Rating - DC2500V (2.5kV)Delectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.693" L x 0.846" W (43.00mm x 21.50mm)Height - Seated (Max)1.516" (38.50mm)PerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-ESR (Equivalent Series Resistance)-Dierating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.693" L x 0.846" W (43.00mm x 21.50mm)Height - Seated (Max)1.516" (38.50mm)FerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	900V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.693" L x 0.846" W (43.00mm x 21.50mm)Height - Seated (Max)1.516" (38.50mm)FerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	2500V (2.5kV)
Derating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.693" L x 0.846" W (43.00mm x 21.50mm)Height - Seated (Max)1.516" (38.50mm)FerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized
NotifiedThrough HoleMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.693" L x 0.846" W (43.00mm x 21.50mm)Height - Seated (Max)1.516" (38.50mm)FerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension1.693" L x 0.846" W (43.00mm x 21.50mm)Height - Seated (Max)1.516" (38.50mm)FerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 110°C
Size / Dimension1.693" L x 0.846" W (43.00mm x 21.50mm)Height - Seated (Max)1.516" (38.50mm)FerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole
Height - Seated (Max)1.516" (38.50mm)FerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	1.693" L x 0.846" W (43.00mm x 21.50mm)
Lead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	1.516" (38.50mm)
Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -	Termination	PC Pins
Features -	Lead Spacing	1.476" (37.50mm)
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT
Report errors?	Features	-
		Report errors?

MKP385420250JPM4T0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

MKP385420250JPM4T0 Payment Methods





MKP385420250JPM4T0 Shipping Methods



If you have any question about MKP385420250JPM4T0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com