

MKP385424025JFI2B0

MKP385424025JFI2B0 Information

Heisener.com	 MKP385424025JFI2B0 Vishay BC Components Capacitors Film Capacitors CAP FILM 0.24UF 5% 250VDC RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP385424025JFI2B0 Specifications

Manufacturer Part NumberMKP385424025JFI2B0ManufacturerVishay BC ComponentsCategoryCapacitorsPackageRadialPackageRadialSeriesMKP385Capacitance0.24µFYoltage Rating - AC160VVoltage Rating - DC250VDielectric MaterialPolypropylene (PP), MetallizedSR (Equivalent Series Resistance)-Operating Type55°C ~ 110°CMounting TypeRadialSize / Dimension0.689° L x 0.197° W (17.50mm x 5.00mm)Height - Seated (Max)0.591° (15.00mm)AdaplactingDC Ins.Lead Spacing0.591° (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-			
Category Capacitors Package Radial Series MKP385 Capacitance 0.24µF Tolerance ±5% Voltage Rating - AC 160V Voltage Rating - DC 250V Dielectric Material Polypropelne (PP), Metallized Portuge Temperature - Operating Type 55°C ~ 110°C Munting Type No.197" W (17.50mm x 5.00mm) Size / Dimension 0.689" L x 0.197" W (17.50mm x 5.00mm) Height - Seated (Max) 0.433" (11.00mm) Lead Spacing 0.591" (15.00mm) Lead Spacing 0.591" (15.00mm) Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Manufacturer Part Number	MKP385424025JFI2B0	
Film CapacitorsPackageRadialSeriesMKP385Capacitance0.24µFTolerance±5%Voltage Rating - AC160VVoltage Rating - DC250VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HoleNouting Type0.689° L x 0.197° W (17.50mm x 5.00mm)Height - Seated (Max)0.433° (11.00mm)TerminationPC PinsLead Spacing0.591° (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components	
PackageRadialSeriesMKP385Capacitance0.24µFTolerance±5%Voltage Rating - AC160VVoltage Rating - DC250VDielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors	
Series MKP385 Capacitance 0.24µF Tolerance ±5% Voltage Rating - AC 160V Voltage Rating - DC 250V Dielectric Material Polypropylene (PP), Metallized Dielectric Material - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.689" L x 0.197" W (17.50mm x 5.00mm) Height - Seated (Max) 0.433" (11.00mm) Fermination DC Pins Lead Spacing 0.591" (15.00mm) Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -		Film Capacitors	
Capacitance0.24μFTolerance±5%Voltage Rating - AC160VVoltage Rating - DC250VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package	Radial	
Tolerance±5%Voltage Rating - AC160VVoltage Rating - DC250VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC L Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Series	MKP385	
Voltage Rating - AC160VVoltage Rating - DC250VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	0.24µF	
Voltage Rating - DC250VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	±5%	
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	160V	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	250V	
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized	
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-	
Package / CaseRadialSize / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 110°C	
Size / Dimension0.689" L x 0.197" W (17.50mm x 5.00mm)Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole	
Height - Seated (Max)0.433" (11.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial	
TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	0.689" L x 0.197" W (17.50mm x 5.00mm)	
Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	0.433" (11.00mm)	
ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Termination	PC Pins	
Features -	Lead Spacing	0.591" (15.00mm)	
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	
	Features	-	
Report errors?		Report errors?	

MKP385424025JFI2B0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

MKP385424025JFI2B0 Payment Methods



MKP385424025JFI2B0 Shipping Methods



If you have any question about MKP385424025JFI2B0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com