

# MKP385427063JFI2B0

### MKP385427063JFI2B0 Information

Heisener.com	 MKP385427063JFI2B0 Vishay BC Components Capacitors Film Capacitors CAP FILM 0.27UF 5% 630VDC RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### MKP385427063JFI2B0 Specifications

Manufacturer Part Number MKP385427063JFI2B0   Manufacturer Vishay BC Components   Category Capacitors   Film Capacitors Film Capacitors   Package Radial   Series MKP385   Capacitance 0.27µF   Tolerance ±5%   Voltage Rating - AC 220V   Voltage Rating - DC 630V   Dielectric Material Polypropylene (PP), Metallized   SPR (Equivalent Series Resistance) -   Operating Temperature -   Operating Type Through Hole   Stace / Case Radial   Stace / Clase 0.650" (16.50mm)   Height - Seated (Max) 0.650" (15.00mm)   Lead Spacing 0.591" (15.00mm)   Applications Dicl.ink, DC Filtering; High Frequency, Switching; High Pulse, DV/DT		
Category Capacitors   Package Radial   Series MKP385   Capacitance 0.27 μF   Tolerance ±5%   Voltage Rating - AC 200V   Voltage Rating - DC 630V   Dielectric Material Polypropylene (PP), Metallized   Operating Temperature -   Operating Type Through Hole   Size / Dimension 0.689" L x 0.394" W (17.50mm x 10.00mm)   Height - Seated (Max) 0.650" (16.50mm)   Lead Spacing 0.591" (15.00mm)   Applications DS1" (15.00mm)   Applications DC1 Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Manufacturer Part Number	MKP385427063JFI2B0
Fin CapacitorsPackageRadialSeriesMKP385Capacitance0.27μFTolerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.650" (16.50mm) x 10.00mm)Height - Seated (Max)0.550" (15.00mm)Lead Spacing0.511" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components
PackageRadiaSeriesMKP385Capacitance0.27µFTolerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.650° (16.50mm) 10.00mm)Height - Seated (Max)0.591° (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors
Series MKP385   Capacitance 0.27µF   Tolerance ±5%   Voltage Rating - AC 200V   Voltage Rating - DC 630V   Dielectric Material Polypropylene (PP), Metallized   Dielectric Material -   Dielectric Material -   Operating Temperature -   Mounting Type Through Hole   Package / Case Radial   Size / Dimension 0.650" (16.50mm)   Height - Seated (Max) 0.550" (15.00mm)   Lead Spacing 0.591" (15.00mm)   Applications Dic Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT   Features -		Film Capacitors
Capacitance0.27μFTolerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package	Radial
Tolerance±5%Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.650" (16.50mm) x10.00mm)Height - Seated (Max)0.551" (15.00mm)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Series	MKP385
Voltage Rating - AC220VVoltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	0.27µF
Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)Termination0.591" (15.00mm)Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	220V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	630V
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 110°C
Size / Dimension0.689" L x 0.394" W (17.50mm x 10.00mm)Height - Seated (Max)0.650" (16.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.650" (16.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	0.689" L x 0.394" W (17.50mm x 10.00mm)
Lead Spacing0.591" (15.00mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	0.650" (16.50mm)
ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.591" (15.00mm)
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT
Report errors?	Features	-
		Report errors?

### MKP385427063JFI2B0 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### MKP385427063JFI2B0 Payment Methods





If you have any question about MKP385427063JFI2B0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com