

MKP385427160JKM2T0 Information

Heisener.com	MKP385427160JKM2T0 Vishay BC Components Capacitors Film Capacitors CAP FILM 0.27UF 5% 1.6KVDC RAD Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP385427160JKM2T0 Specifications

SeriesMKP385Capacitance0.27μFTolerance±5%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsApplications0.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT		
CategoryCapacitorsPackageRadialPackageRadialSeriesMKP385Capacitance0.27μFTolerance±5%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedStr (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240° L x 0.709° W (31.50mm x 18.00mm)Height - Seated (Max)1.100° (28.00mm)TerminationPC PinsLead Spacing1.083° (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer Part Number	MKP385427160JKM2T0
Film CapacitorsPackageRadialSeriesMKP385Capacitance0.27μFTolerance±5%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240° L x 0.709° W (31.50mm x 18.00mm)Height - Seated (Max)1.000° (28.00mm)Lead Spacing1.083° (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components
PackageRadiaSeriesMKP385Capacitance0.27µFTolerance±5%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240° L x 0.709° W (31.50mm x 18.00mm)Height - Seated (Max)1.100° (28.00mm)Lead Spacing0C Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors
Series MKP385 Capacitance 0.27µF Tolerance ±5% Voltage Rating - AC 550V Voltage Rating - DC 1600V (1.6kV) Dielectric Material Polypropylene (PP), Metallized DSR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.240" L x 0.709" W (31.50mm x 18.00mm) Height - Seated (Max) 1.00" (28.00mm) Termination PC Pins Lead Spacing 1.083" (27.50mm) Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -		Film Capacitors
Capacitance0.27μFTolerance±5%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)Applications-Features-	Package	Radial
Tolerance±5%Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)Applications-Features-	Series	MKP385
Voltage Rating - AC550VVoltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	0.27µF
Voltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240° L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	±5%
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	550V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	1600V (1.6kV)
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 110°C
Size / Dimension1.240" L x 0.709" W (31.50mm x 18.00mm)Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole
Height - Seated (Max)1.100" (28.00mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	1.240" L x 0.709" W (31.50mm x 18.00mm)
Lead Spacing1.083" (27.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	1.100" (28.00mm)
ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Termination	PC Pins
Features -	Lead Spacing	1.083" (27.50mm)
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT
Report errors?	Features	-
		Report errors?

MKP385427160JKM2T0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MKP385427160JKM2T0 Payment Methods



If you have any question about MKP385427160JKM2T0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com