

MKP385475125JPM2T0

MKP385475125JPM2T0 Information







Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP385475125JPM2T0 Specifications

Manufacturer Vishay BC Components Category Capacitors Film Capacitors Film Capacitors Package Radial Series MKP385 Capacitance 0.75µF Tolerance ±5% Voltage Rating - AC 450V Voltage Rating - DC 1250V (1.25kV) Dielectric Material Polypropylene (PP), Metallized Poprating Temperature - Operating Temperature -S5°C ~ 110°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.634" L x 0.630" W (41.50mm x 16.00mm) Height - Seated (Max) 1.122" (28.50mm) Lead Spacing 1.476" (37.50mm)		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesMKP385Capacitance0.75µFTolerance±5%Voltage Rating - AC450VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.630" W (41.50mm x 16.00mm)Height - Seated (Max)1.122" (28.50mm)Lead Spacing1.476" (37.50mm)	Manufacturer Part Number	MKP385475125JPM2T0
Fin CapacitorsPackageRadialPackageMKP385Capacitance0.75μFTolerance±5%Voltage Rating - AC450VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.630" W (41.50mm x 16.00mm)Height - Seated (Max)1.122" (28.50mm)Lead Spacing1.476" (37.50mm)	Manufacturer	Vishay BC Components
PackageRadialPackageRadialSeriesMKP385Capacitance0.75µFTolerance±5%Voltage Rating - AC450VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.630" W (41.50mm x 16.00mm)Height - Seated (Max)1.122" (28.50mm)Lead Spacing1.476" (37.50mm)	Category	Capacitors
SeriesMKP385Capacitance0.75μFTolerance±5%Voltage Rating - AC450VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.630" W (41.50mm x 16.00mm)Height - Seated (Max)1.122" (28.50mm)Lead Spacing1.476" (37.50mm)		Film Capacitors
Capacitance0.75μFTolerance±5%Voltage Rating - AC450VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.630" W (41.50mm x 16.00mm)Height - Seated (Max)1.122" (28.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)	Package	Radial
Tolerance±5%Voltage Rating - AC450VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.630" W (41.50mm x 16.00mm)Height - Seated (Max)1.122" (28.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)	Series	MKP385
Voltage Rating - AC450VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.630" W (41.50mm x 16.00mm)Height - Seated (Max)1.122" (28.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)	Capacitance	0.75µF
Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.630" W (41.50mm x 16.00mm)Height - Seated (Max)1.122" (28.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.630" W (41.50mm x 16.00mm)Height - Seated (Max)1.122" (28.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)	Voltage Rating - AC	450V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.630" W (41.50mm x 16.00mm)Height - Seated (Max)1.122" (28.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)	Voltage Rating - DC	1250V (1.25kV)
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.630" W (41.50mm x 16.00mm)Height - Seated (Max)1.122" (28.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)	Dielectric Material	Polypropylene (PP), Metallized
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.630" W (41.50mm x 16.00mm)Height - Seated (Max)1.122" (28.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension1.634" L x 0.630" W (41.50mm x 16.00mm)Height - Seated (Max)1.122" (28.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)	Operating Temperature	-55°C ~ 110°C
Size / Dimension 1.634" L x 0.630" W (41.50mm x 16.00mm) Height - Seated (Max) 1.122" (28.50mm) Termination PC Pins Lead Spacing 1.476" (37.50mm)	Mounting Type	Through Hole
Height - Seated (Max)1.122" (28.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)	Package / Case	Radial
TerminationPC PinsLead Spacing1.476" (37.50mm)	Size / Dimension	1.634" L x 0.630" W (41.50mm x 16.00mm)
Lead Spacing 1.476" (37.50mm)	Height - Seated (Max)	1.122" (28.50mm)
	Termination	PC Pins
Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT	Lead Spacing	1.476" (37.50mm)
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT
Features -	Features	-
Report errors?		Report errors?

MKP385475125JPM2T0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

MKP385475125JPM2T0 Payment Methods





MKP385475125JPM2T0 Shipping Methods



If you have any question about MKP385475125JPM2T0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com