

MKP385543125JYM5T0

MKP385543125JYM5T0 Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP385543125JYM5T0 Specifications

ManufacturerVishay BC ComponentsCapacitorsFilm CapacitorsPackageRadialSeriesMKP385Capacitance4.3µFTolerance±5%Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-5%C ~ 110°CPackage / CaseRadialSize / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)TerminationPC PinsLad Spacing2.067" (52.50mm)ApplicationsJC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-		
CategoryCapacitorsPackageRadialPackageRadialSeriesMKP385Capacitors4.3µFTolerance±5%Voltage Rating - AC450VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer Part Number	MKP385543125JYM5T0
Fin CapacitorsPackageRadialSeriesMKP385Capacitance4.3μFTolerance±5%Voltage Rating - AC450VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC L Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components
PackageRadialSeriesMKP385Capacitance4.3µFTolerance±5%Voltage Rating - AC450VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)TerminationPC PinsLead Spacing.067" (52.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors
Series MKP385 Capacitance 4.3µF Tolerance ±5% Voltage Rating - AC 450V Voltage Rating - DC 1250V (1.25kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.260" (50.00mm) Height - Seated (Max) 1.969" (50.00mm) Termination PC Pins Lead Spacing 2.067" (52.50mm) Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT		Film Capacitors
Capacitance4.3μFTolerance±5%Voltage Rating - AC450VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package	Radial
Tolerance±5%Voltage Rating - AC450VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Series	MKP385
Voltage Rating - AC450VVoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	4.3µF
Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	450V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	1250V (1.25kV)
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 110°C
Size / Dimension2.264" L x 1.378" W (57.50mm x 35.00mm)Height - Seated (Max)1.969" (50.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole
Height - Seated (Max)1.969" (50.00mm)TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	2.264" L x 1.378" W (57.50mm x 35.00mm)
Lead Spacing2.067" (52.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	1.969" (50.00mm)
ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Termination	PC Pins
Features -	Lead Spacing	2.067" (52.50mm)
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT
Report errors?	Features	-
		Report errors?

MKP385543125JYM5T0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

စ္ခ် MoneyGram <u>Alipay</u> VISA

DISCOVER

MKP385543125JYM5T0 Payment Methods



MKP385543125JYM5T0 Shipping Methods



If you have any question about MKP385543125JYM5T0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com

 \mathbf{M}