

# MKP385547040JPI2T0

### MKP385547040JPI2T0 Information

Heisener.com	MKP385547040JPI2T0 Vishay BC Components Capacitors Film Capacitors CAP FILM 4.7UF 5% 400VDC RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### MKP385547040JPI2T0 Specifications

ManufacturerVishay BC ComponentsCapacitorsFilm CapacitorsPackageRadialSeriesRdBaCapacitance4.7µFVoltage Rating - DC200VVoltage Rating - DC400VDielectric Material-Porsphere (PP), Metallized-Operating Temperature-Voltage Jeance-Nouting Type-Package / CaseRadialSiz / Dimension1.634" L x 0.709" W (41.50mm x 18.00mm)Height - Seated (Max)1.280" (32.50mm)Height - Seated (Max)1.476" (37.50mm)ApplicationsDielectric Sitting ; High Frequency, Switching ; High Pulse, DV/DT		
Category Capacitors   Film Capacitors Film Capacitors   Package Radial   Series MKP385   Capacitance 4.7µF   Tolerance ±5%   Voltage Rating - AC 200V   Voltage Rating - DC 400V   Dielectric Material Polypropylene (PP), Metallized   Series Resistance) -   Operating Temperature -55°C ~ 110°C   Mounting Type Through Hole   Package / Case Radial   Size / Dimension 1.634° L x 0.709° W (41.50mm x 18.00mm)   Height - Seated (Max) 1.280° (32.50mm)   Termination PC Pins   Lead Spacing .   Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT   Features -	Manufacturer Part Number	MKP385547040JPI2T0
Film CapacitorsPackageRadialSeriesMKP385Capacitance4.7µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.709" W (41.50mm x 18.00mm)Height - Seated (Max)1.280" (32.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Llink, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components
PackageRadialSeriesMKP385Capacitance4.7µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.709" W (41.50mm x 18.00mm)Height - Seated (Max)1.280" (32.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors
Series MKP385   Capacitance 4.7μF   Tolerance ±5%   Voltage Rating - AC 200V   Voltage Rating - DC 400V   Dielectric Material Polypropylene (PP), Metallized   ESR (Equivalent Series Resistance) -   Operating Temperature -55°C ~ 110°C   Mounting Type Through Hole   Package / Case Radial   Size / Dimension 1.634" L x 0.709" W (41.50mm x 18.00mm)   Height - Seated (Max) 1.280" (32.50mm)   Lead Spacing 1.476" (37.50mm)   Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT   Features -		Film Capacitors
Capacitance4.7µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.709" W (41.50mm x 18.00mm)Height - Seated (Max)1.280" (32.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)Applications-Features-	Package	Radial
Tolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.709" W (41.50mm x 18.00mm)Height - Seated (Max)1.280" (32.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)Applications-Features-	Series	MKP385
Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.709" W (41.50mm x 18.00mm)Height - Seated (Max)1.280" (32.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	4.7μF
Voltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.709" W (41.50mm x 18.00mm)Height - Seated (Max)1.280" (32.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.709" W (41.50mm x 18.00mm)Height - Seated (Max)1.280" (32.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	200V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.709" W (41.50mm x 18.00mm)Height - Seated (Max)1.280" (32.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	400V
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.709" W (41.50mm x 18.00mm)Height - Seated (Max)1.280" (32.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension1.634" L x 0.709" W (41.50mm x 18.00mm)Height - Seated (Max)1.280" (32.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension1.634" L x 0.709" W (41.50mm x 18.00mm)Height - Seated (Max)1.280" (32.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 110°C
Size / Dimension1.634" L x 0.709" W (41.50mm x 18.00mm)Height - Seated (Max)1.280" (32.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole
Height - Seated (Max)1.280" (32.50mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	1.634" L x 0.709" W (41.50mm x 18.00mm)
Lead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	1.280" (32.50mm)
ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Termination	PC Pins
Features -	Lead Spacing	1.476" (37.50mm)
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT
Report errors?	Features	-
		Report errors?

### MKP385547040JPI2T0 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### MKP385547040JPI2T0 Payment Methods



If you have any question about MKP385547040JPI2T0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com