

MKP385551085JPM5T0

MKP385551085JPM5T0 Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKP385551085JPM5T0 Specifications

ManufacturerVishay BC ComponentsCategoryCapacitorsFilm CapacitorsPackageRadialSeriesMKP385Capacitance5.1µFTolerance±5%Voltage Rating - DC300VVoltage Rating - DC850VDielectric MaterialPolypropylene (PP), MetallizedSories-Operating Temperature-5°C ~ 110°CVoltage / CaseRadialSize / Dimension1.654" L x 1.181" W (42.00mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-		
Category Capacitors Film Capacitors Film Capacitors Package Radial Series MKP385 Capacitors 5.1µF Tolerance ±5% Voltage Rating - AC 300V Voltage Rating - DC 850V Dielectric Material Polypropulene (PP), Metallized Operating Temperature - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Size / Dimension 1.654" L x 1.181" W (42.00mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) PC Pins Lead Spacing Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -	Manufacturer Part Number	MKP385551085JPM5T0
Fin CapacitorsPackageRadialSeriesMKP385Capacitance5.1μFTolerance±5%Voltage Rating - AC300VVoltage Rating - DC850VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.654" L x 1.181" W (42.00mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationspC L Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Vishay BC Components
PackageRadialSeriesMKP385Capacitance5.1µFTolerance±5%Voltage Rating - AC300VVoltage Rating - DC850VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.654" L x 1.181" W (42.00mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)CerninationPC PinsLead Spacing1.476" (37.50mm)ApplicationsPC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors
Arror MKP385 Series MKP385 Capacitance 5.1µF Tolerance ±5% Voltage Rating - AC 300V Voltage Rating - DC 850V Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 110°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.654" L x 1.181" W (42.00mm x 30.00mm) Height - Seated (Max) 1.772" (45.00mm) Lead Spacing 1.476" (37.50mm) Applications DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT Features -		Film Capacitors
Capacitance5.1µFTolerance±5%Voltage Rating - AC300VVoltage Rating - DC850VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.654" L x 1.181" W (42.00mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)Applications-Features-	Package	Radial
Tolerance±5%Voltage Rating - AC300VVoltage Rating - DC850VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.654" L x 1.181" W (42.00mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Series	MKP385
Voltage Rating - AC300VVoltage Rating - DC850VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.654" L x 1.181" W (42.00mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	5.1µF
Voltage Rating - DC850VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.654" L x 1.181" W (42.00mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.654" L x 1.181" W (42.00mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	300V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.654" L x 1.181" W (42.00mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	850V
Operating Temperature-55°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.654" L x 1.181" W (42.00mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension1.654" L x 1.181" W (42.00mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension1.654" L x 1.181" W (42.00mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 110°C
Size / Dimension1.654" L x 1.181" W (42.00mm x 30.00mm)Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Through Hole
Height - Seated (Max)1.772" (45.00mm)TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	1.654" L x 1.181" W (42.00mm x 30.00mm)
Lead Spacing1.476" (37.50mm)ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	1.772" (45.00mm)
ApplicationsDC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DTFeatures-	Termination	PC Pins
Features -	Lead Spacing	1.476" (37.50mm)
	Applications	DC Link, DC Filtering; High Frequency, Switching; High Pulse, DV/DT
Report errors?	Features	-
		Report errors?

MKP385551085JPM5T0 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

MKP385551085JPM5T0 Payment Methods



MKP385551085JPM5T0 Shipping Methods



If you have any question about MKP385551085JPM5T0, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com