

# MKP386M439200JT1

#### MKP386M439200JT1 Information





Request a Quote

For Reference Only

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### MKP386M439200JT1 Specifications

Manufacturer Part NumberMKP386M439200T1ManufacturerVishay BC ComponentsCategoryCapacitorsPackageRetangular BoxPackageMKP386MCapacitance0.39µFTolerance45%Voltage Rating - AC00V (2kV)Dielectric Material90ypopylene (PP), MetallizedDoprating Temperature6mOhnOperating Type6kasi MountPackage / Case7.32° L x 0.866° W (44.00mm x 22.00mm)Fight - Seated (Max)1.496° (38.00mm)Fight - Seated (Max)6kasi MountLead Spacing6kasi MountFight - Seated (Max)1.496° (38.00mm)Fight - Seated (Max)6kasi MountLead Spacing6kasi MountFight - Seated (Max)1.496° (38.00mm)Fight - Seated (Max)6kasi MountLead Spacing6kasi MountFight - Seated (Max)6kasi Mount		
CategoryCapacitorsFilm CapacitorsPackageRectangular BoxSeriesMKP386MCapacitance0.39µFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)6 mOhmOperating Temperature-55°C ~ 105°CMounting TypeChasis MountSize / Dimension1.732" L x 0.866" W (44.00mm x 22.00mm)Height - Seated (Max)1.496" (38.00mm)TerminationScrew TerminalsLead Spacing0.402" (10.20mm)ApplicationsSnubber	Manufacturer Part Number	MKP386M439200JT1
Him CapacitorsPackageRectangular BoxSeriesMKP386MCapacitance0.39µFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)6 mOhmOperating Temperature-55°C ~ 105°CMounting TypeChassis MountSize / Dimension1.732" L x 0.866" W (44.00mm x 22.00mm)Height - Seated (Max)1.496" (38.00mm)TerminationScrew TerminalsLead Spacing0.402" (10.20mm)ApplicationsSnubber	Manufacturer	Vishay BC Components
PackageRectangular BoxSeriesMKP386MCapacitance0.39µFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedSSR (Equivalent Series Resistance)6 mOhmOperating Temperature-55°C ~ 105°CMounting TypeRectangular BoxSize / Dimension1.732" L x 0.866" W (44.00mm x 22.00mm)Height - Seated (Max)1.496" (38.00mm)Lead Spacing0.402" (10.20mm)ApplicationsSnubber	Category	Capacitors
SeriesMKP386MCapacitance0.39µFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)6 mOhmOperating Temperature-55°C ~ 105°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension1.732" L x 0.866" W (44.00mm x 22.00mm)Height - Seated (Max)1.496" (38.00mm)Lead Spacing0.402" (10.20mm)ApplicationsSnubber		Film Capacitors
Capacitance0.39μFTolerance±5%Voltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material6 mOhmOperating Temperature55°C ~ 105°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension1.472°L x 0.866°W (44.00mm x 22.00mm)Height - Seated (Max)1.496° (38.00mm)Lead Spacing0.402° (10.20mm)ApplicationsSnubber	Package	Rectangular Box
Tolerance±5%Yoltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)6 mOhmOperating Temperature-55°C ~ 105°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension1.732" L x 0.866" W (44.00mm x 22.00mm)Height - Seated (Max)1.496" (38.00mm)TerminationScrew TerminalsLead Spacing0.402" (10.20mm)ApplicationsSnubber	Series	MKP386M
NoteVoltage Rating - AC700VVoltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)6 mOhmOperating Temperature-55°C ~ 105°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension1.732" L x 0.866" W (44.00mm x 22.00mm)Height - Seated (Max)1.496" (38.00mm)TerminationScrew TerminalsLead Spacing0.402" (10.20mm)ApplicationsSnubber	Capacitance	0.39µF
Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)6 mOhmOperating Temperature-55°C ~ 105°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension1.732" L x 0.866" W (44.00mm x 22.00mm)Height - Seated (Max)1.496" (38.00mm)TerminationScrew TerminalsLead Spacing0.402" (10.20mm)ApplicationsSnubber	Tolerance	±5%
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)6 mOhmOperating Temperature-55°C ~ 105°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension1.732" L x 0.866" W (44.00mm x 22.00mm)Height - Seated (Max)1.496" (38.00mm)TerminationScrew TerminalsLead Spacing0.402" (10.20mm)ApplicationsSnubber	Voltage Rating - AC	700V
ESR (Equivalent Series Resistance)6 mOhmOperating Temperature-55°C ~ 105°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension1.732" L x 0.866" W (44.00mm x 22.00mm)Height - Seated (Max)1.496" (38.00mm)TerminationScrew TerminalsLead Spacing0.402" (10.20mm)ApplicationsSnubber	Voltage Rating - DC	2000V (2kV)
Operating Temperature-55°C ~ 105°CMounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension1.732" L x 0.866" W (44.00mm x 22.00mm)Height - Seated (Max)1.496" (38.00mm)TerminationScrew TerminalsLead Spacing0.402" (10.20mm)ApplicationsSnubber	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeChassis MountPackage / CaseRectangular BoxSize / Dimension1.732" L x 0.866" W (44.00mm x 22.00mm)Height - Seated (Max)1.496" (38.00mm)TerminationScrew TerminalsLead Spacing0.402" (10.20mm)ApplicationsSnubber	ESR (Equivalent Series Resistance)	6 mOhm
Package / CaseRectangular BoxSize / Dimension1.732" L x 0.866" W (44.00mm x 22.00mm)Height - Seated (Max)1.496" (38.00mm)TerminationScrew TerminalsLead Spacing0.402" (10.20mm)ApplicationsSnubber	Operating Temperature	-55°C ~ 105°C
Size / Dimension     1.732" L x 0.866" W (44.00mm x 22.00mm)       Height - Seated (Max)     1.496" (38.00mm)       Termination     Screw Terminals       Lead Spacing     0.402" (10.20mm)       Applications     Snubber	Mounting Type	Chassis Mount
Height - Seated (Max)1.496" (38.00mm)TerminationScrew TerminalsLead Spacing0.402" (10.20mm)ApplicationsSnubber	Package / Case	Rectangular Box
TerminationScrew TerminalsLead Spacing0.402" (10.20mm)ApplicationsSnubber	Size / Dimension	1.732" L x 0.866" W (44.00mm x 22.00mm)
Lead Spacing0.402" (10.20mm)ApplicationsSnubber	Height - Seated (Max)	1.496" (38.00mm)
Applications Snubber	Termination	Screw Terminals
	Lead Spacing	0.402" (10.20mm)
Features Low ESR	Applications	Snubber
	Features	Low ESR
Report errors?		Report errors?

E-mail: salesdept@heisener.com

#### MKP386M439200JT1 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### MKP386M439200JT1 Payment Methods





If you have any question about MKP386M439200JT1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com