



### **MKS1T-10 AC120 Information**

Heisener.com

Part Number MKS1T-10 AC120

Manufacturer Omron Automation and Safety

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 15A 120V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MKS1T-10 AC120 Specifications**

Manufacturer Part Number     MKS1T-10 AC120       Manufacturer     Omron Automation and Safety       Category     Relays       Power Relays, Over 2 Amps       Package     -       Series     MKS-X       Relay Type     General Purpose       Coil Type     Non Latching       Coil Current     19.3mA       Coil Voltage     120VAC       Contact Form     SPST-NO (1 Form A)       Contact Rating (Current)     15A       Switching Voltage     250VAC - Max       Turn On Voltage (Max)     96 VAC       Turn Off Voltage (Min)     36 VAC       Operate Time     20ms       Release Time     20ms       Features     -       Mounting Type     Socketable       Termination Style     Plug In		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         MKS-X           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         19.3mA           Coil Voltage         120VAC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         15A           Switching Voltage         250VAC - Max           Turn On Voltage (Max)         96 VAC           Turn Off Voltage (Min)         36 VAC           Operate Time         20ms           Release Time         20ms           Features         -           Mounting Type         Socketable           Termination Style         Plug In	Manufacturer Part Number	MKS1T-10 AC120
Package-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19.3mACoil Voltage120VACContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package         -           Series         MKS-X           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         19.3mA           Coil Voltage         120VAC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         15A           Switching Voltage         250VAC - Max           Turn On Voltage (Max)         96 VAC           Turn Off Voltage (Min)         36 VAC           Operate Time         20ms           Release Time         20ms           Features         -           Mounting Type         Socketable           Termination Style         Plug In	Category	Relays
SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current19.3mACoil Voltage120VACContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 19.3mA Coil Voltage 120VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current19.3mACoil Voltage120VACContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Series	MKS-X
Coil Current 19.3mA Coil Voltage 120VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 96 VAC Turn Off Voltage (Min) 36 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Relay Type	General Purpose
Coil Voltage120VACContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 15A  Switching Voltage 250VAC - Max  Turn On Voltage (Max) 96 VAC  Turn Off Voltage (Min) 36 VAC  Operate Time 20ms  Release Time 20ms  Features - Mounting Type Socketable  Termination Style Plug In	Coil Current	19.3mA
Contact Rating (Current)  Switching Voltage  250VAC - Max  Turn On Voltage (Max)  96 VAC  Turn Off Voltage (Min)  36 VAC  Operate Time  20ms  Release Time  20ms  Features  -  Mounting Type  Socketable  Termination Style	Coil Voltage	120VAC
Switching Voltage 250VAC - Max  Turn On Voltage (Max) 96 VAC  Turn Off Voltage (Min) 36 VAC  Operate Time 20ms  Release Time 20ms  Features -  Mounting Type Socketable  Termination Style Plug In	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  7urn Off Voltage (Min)  96 VAC  Operate Time  20ms  Release Time  20ms  Features  -  Mounting Type  Socketable  Termination Style  96 VAC  96 VAC  96 VAC  96 VAC  10 Socketable  Plug In	Contact Rating (Current)	15A
Turn Off Voltage (Min)  Operate Time  20ms  Release Time  20ms  Features  -  Mounting Type  Socketable  Termination Style  Plug In	Switching Voltage	250VAC - Max
Operate Time 20ms  Release Time 20ms  Features -  Mounting Type Socketable  Termination Style Plug In	Turn On Voltage (Max)	96 VAC
Release Time 20ms  Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	36 VAC
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

### MKS1T-10 AC120 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# MKS1T-10 AC120 Payment Methods



















### **MKS1T-10 AC120 Shipping Methods**













If you have any question about MKS1T-10 AC120, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com