



### **MKS1TI-10 DC48 Information**

Heisener.com

Part Number MKS1TI-10 DC48

Manufacturer Omron Automation and Safety

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 15A 48V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MKS1TI-10 DC48 Specifications**

| Manufacturer Part NumberMKS1TI-10 DC48ManufacturerOmron Automation and SafetyCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current32mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)7.2 VDCOperate Time30ms  |                          |                             |
|---|--------------------------|-----------------------------|
| Category Relays Power Relays, Over 2 Amps  Package - Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 32mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 7.2 VDC   | Manufacturer Part Number | MKS1TI-10 DC48              |
| Package - Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 32mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 7.2 VDC   | Manufacturer             | Omron Automation and Safety |
| Package         -           Series         MKS-X           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         32mA           Coil Voltage         48VDC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         15A           Switching Voltage         250VAC - Max           Turn On Voltage (Max)         38.4 VDC           Turn Off Voltage (Min)         7.2 VDC | Category                 | Relays                      |
| Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 32mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 7.2 VDC   |                          | Power Relays, Over 2 Amps   |
| Relay Type General Purpose  Coil Type Non Latching  Coil Current 32mA  Coil Voltage 48VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 15A  Switching Voltage 250VAC - Max  Turn On Voltage (Max) 38.4 VDC  Turn Off Voltage (Min) 7.2 VDC  | Package                  | -                           |
| Coil TypeNon LatchingCoil Current32mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)7.2 VDC  | Series                   | MKS-X                       |
| Coil Current 32mA  Coil Voltage 48VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 15A  Switching Voltage 250VAC - Max  Turn On Voltage (Max) 38.4 VDC  Turn Off Voltage (Min) 7.2 VDC  | Relay Type               | General Purpose             |
| Coil Voltage 48VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 15A  Switching Voltage 250VAC - Max  Turn On Voltage (Max) 38.4 VDC  Turn Off Voltage (Min) 7.2 VDC   | Coil Type                | Non Latching                |
| Contact Form SPST-NO (1 Form A)  Contact Rating (Current)  Switching Voltage  250VAC - Max  Turn On Voltage (Max)  38.4 VDC  Turn Off Voltage (Min)  7.2 VDC  | Coil Current             | 32mA                        |
| Contact Rating (Current)  Switching Voltage  250VAC - Max  Turn On Voltage (Max)  38.4 VDC  Turn Off Voltage (Min)  7.2 VDC   | Coil Voltage             | 48VDC                       |
| Switching Voltage 250VAC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 7.2 VDC  | Contact Form             | SPST-NO (1 Form A)          |
| Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 7.2 VDC   | Contact Rating (Current) | 15A                         |
| Turn Off Voltage (Min) 7.2 VDC  | Switching Voltage        | 250VAC - Max                |
| - 1   | Turn On Voltage (Max)    | 38.4 VDC                    |
| Operate Time 30ms   | Turn Off Voltage (Min)   | 7.2 VDC                     |
|   | Operate Time             | 30ms                        |
| Release Time 20ms   | Release Time             | 20ms                        |
| Features Test Button  | Features                 | Test Button                 |
| Mounting Type Socketable  | Mounting Type            | Socketable                  |
| Termination Style Plug In   | Termination Style        | Plug In                     |
| Report errors?  |                          | Report errors?              |

#### MKS1TI-10 DC48 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **MKS1TI-10 DC48 Payment Methods**





















## **MKS1TI-10 DC48 Shipping Methods**













If you have any question about MKS1TI-10 DC48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com