



MKS1TIN-10 DC48 Information

Heisener.com

Part Number MKS1TIN-10 DC48

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 15A 48V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MKS1TIN-10 DC48 Specifications

Manufacturer Part Number Manufacturer Omron Automation and Safety Relays Power Relays, Over 2 Amps Package		
Category Relays Power Relays, Over 2 Amps Package	Manufacturer Part Number	MKS1TIN-10 DC48
Package-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current32mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)7.2 VDCOperate Time30msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current32mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)7.2 VDCOperate Time30msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Category	Relays
SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current32mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)7.2 VDCOperate Time30msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 32mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current32mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)7.2 VDCOperate Time30msRelease Time20msFeaturesLED Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In	Series	MKS-X
Coil Current Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Coil Current	32mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Coil Voltage	48VDC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Contact Rating (Current)	15A
Turn Off Voltage (Min) Operate Time 30ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC - Max
Operate Time 30ms Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	38.4 VDC
Release Time 20ms Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	7.2 VDC
Features LED Indicator, Test Button Mounting Type Socketable Termination Style Plug In	Operate Time	30ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	LED Indicator, Test Button
	Mounting Type	Socketable
Papart arrors?	Termination Style	Plug In
Report errors:		Report errors?

MKS1TIN-10 DC48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MKS1TIN-10 DC48 Payment Methods





















MKS1TIN-10 DC48 Shipping Methods













If you have any question about MKS1TIN-10 DC48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com