



MKS1TN-10 AC110 Information

Heisener.com

Part Number MKS1TN-10 AC110

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 15A 110V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MKS1TN-10 AC110 Specifications

Manufacturer Part Number MKS1TN-10 AC110 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 21mA Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPackage-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current21mACoil Voltage110VACContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	MKS1TN-10 AC110
Package Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 21mA Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style	Manufacturer	Omron Automation and Safety
Package-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current21mACoil Voltage110VACContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Category	Relays
SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current21mACoil Voltage110VACContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type Coil Type Non Latching Coil Current 21mA Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Release Time 1ED Indicator Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current21mACoil Voltage110VACContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Series	MKS-X
Coil Current Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Current	21mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style	Coil Voltage	110VAC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Contact Rating (Current)	15A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC - Max
Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	88 VAC
Release Time 20ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	33 VAC
Features LED Indicator Mounting Type Socketable Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	LED Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

MKS1TN-10 AC110 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MKS1TN-10 AC110 Payment Methods



















MKS1TN-10 AC110 Shipping Methods













If you have any question about MKS1TN-10 AC110, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com