



MKS1TN-10 AC240 Information

Heisener.com

Part Number MKS1TN-10 AC240

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 15A 240V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MKS1TN-10 AC240 Specifications

Manufacturer Part NumberMKS1TN-10 AC240ManufacturerOmron Automation and SafetyCategoryRelays Power Relays, Over 2 AmpsPackage-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.6mACoil Voltage240VACContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketable		
CategoryRelaysPackage-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.6mACoil Voltage240VACContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketable	Manufacturer Part Number	MKS1TN-10 AC240
Package - Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 9.6mA Coil Voltage 240VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable	Manufacturer	Omron Automation and Safety
Package-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.6mACoil Voltage240VACContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketable	Category	Relays
SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.6mACoil Voltage240VACContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketable		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 9.6mA Coil Voltage 240VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Release Time LED Indicator Mounting Type Socketable	Package	-
Coil TypeNon LatchingCoil Current9.6mACoil Voltage240VACContact FormSPST-NO (1 Form A)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesLED IndicatorMounting TypeSocketable	Series	MKS-X
Coil Current 9.6mA Coil Voltage 240VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Release Time LED Indicator Mounting Type Socketable	Relay Type	General Purpose
Coil Voltage 240VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable	Coil Current	9.6mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable	Coil Voltage	240VAC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable	Contact Rating (Current)	15A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable	Switching Voltage	250VAC - Max
Operate Time 20ms Release Time 20ms Features LED Indicator Mounting Type Socketable	Turn On Voltage (Max)	192 VAC
Release Time 20ms Features LED Indicator Mounting Type Socketable	Turn Off Voltage (Min)	72 VAC
Features LED Indicator Mounting Type Socketable	Operate Time	20ms
Mounting Type Socketable	Release Time	20ms
	Features	LED Indicator
m ' ' ' ' ' G. 1	Mounting Type	Socketable
remination style Plug In	Termination Style	Plug In
Report errors?		Report errors?

MKS1TN-10 AC240 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MKS1TN-10 AC240 Payment Methods





















MKS1TN-10 AC240 Shipping Methods













If you have any question about MKS1TN-10 AC240, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com