



### MKS1XTI-10 AC24 Information

Heisener.com

Part Number MKS1XTI-10 AC24

Manufacturer Omron Automation and Safety

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 10A 24V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MKS1XTI-10 AC24 Specifications**

Manufacturer Part NumberMKS1XTI-10 AC24ManufacturerOmron Automation and SafetyCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current96.3mACoil Voltage24VACContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage220VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time20msRelease Time20msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In		
CategoryRelaysPackage-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current96.3mACoil Voltage24VACContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage220VDC - MaxTurn On Voltage (Max)19.2 VACOperate Time20msRelease Time20msFeaturesTest ButtonMounting TypeSocketable	Manufacturer Part Number	MKS1XTI-10 AC24
Package - Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 96.3mA Coil Voltage 24VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 20ms Release Time 20ms Features Test Button Mounting Type Socketable	Manufacturer	Omron Automation and Safety
Package-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current96.3mACoil Voltage24VACContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage220VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time20msRelease Time20msFeaturesTest ButtonMounting TypeSocketable	Category	Relays
SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current96.3mACoil Voltage24VACContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage220VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time20msRelease Time20msFeaturesTest ButtonMounting TypeSocketable		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 96.3mA Coil Voltage 24VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 20ms Release Time 20ms Release Time 20ms Features Test Button Mounting Type Socketable	Package	-
Coil TypeNon LatchingCoil Current96.3mACoil Voltage24VACContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage220VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time20msRelease Time20msFeaturesTest ButtonMounting TypeSocketable	Series	MKS-X
Coil Current96.3mACoil Voltage24VACContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage220VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time20msRelease Time20msFeaturesTest ButtonMounting TypeSocketable	Relay Type	General Purpose
Coil Voltage24VACContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage220VDC - MaxTurn On Voltage (Max)19.2 VACTurn Off Voltage (Min)7.2 VACOperate Time20msRelease Time20msFeaturesTest ButtonMounting TypeSocketable	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 10A  Switching Voltage 220VDC - Max  Turn On Voltage (Max) 19.2 VAC  Turn Off Voltage (Min) 7.2 VAC  Operate Time 20ms  Release Time 20ms  Features Test Button  Mounting Type Socketable	Coil Current	96.3mA
Contact Rating (Current)  Switching Voltage  220VDC - Max  Turn On Voltage (Max)  19.2 VAC  Turn Off Voltage (Min)  7.2 VAC  Operate Time  20ms  Release Time  20ms  Features  Test Button  Mounting Type  Socketable	Coil Voltage	24VAC
Switching Voltage 220VDC - Max Turn On Voltage (Max) 19.2 VAC Turn Off Voltage (Min) 7.2 VAC Operate Time 20ms Release Time 20ms Features Test Button Mounting Type Socketable	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  19.2 VAC  Turn Off Voltage (Min)  7.2 VAC  Operate Time  20ms  Release Time  20ms  Features  Test Button  Mounting Type  Socketable	Contact Rating (Current)	10A
Turn Off Voltage (Min) 7.2 VAC Operate Time 20ms Release Time 20ms Features Test Button Mounting Type Socketable	Switching Voltage	220VDC - Max
Operate Time20msRelease Time20msFeaturesTest ButtonMounting TypeSocketable	Turn On Voltage (Max)	19.2 VAC
Release Time 20ms Features Test Button Mounting Type Socketable	Turn Off Voltage (Min)	7.2 VAC
Features Test Button Mounting Type Socketable	Operate Time	20ms
Mounting Type Socketable	Release Time	20ms
	Features	Test Button
Termination Style Plug In	Mounting Type	Socketable
	Termination Style	Plug In
Report errors?		Report errors?

### MKS1XTI-10 AC24 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MKS1XTI-10 AC24 Payment Methods



















### MKS1XTI-10 AC24 Shipping Methods













If you have any question about MKS1XTI-10 AC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com