



MKS1XTI-10 DC24 Information



For Reference Only

Part Number MKS1XTI-10 DC24

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 10A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MKS1XTI-10 DC24 Specifications

Manufacturer Part Number MKS1XTI-10 DC24 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 63.2mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 3.6 VDC
Category Relays Power Relays, Over 2 Amps Package - Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 63.2mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 19.2 VDC
Power Relays, Over 2 Amps Package - Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 63.2mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) Switching Voltage 19.2 VDC Turn On Voltage (Max) Power Relays, Over 2 Amps - I Amps Series MKS-X General Purpose Non Latching 63.2mA 24VDC 24VDC 24VDC 10A
Package - MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 63.2mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) Switching Voltage 220VDC - Max Turn On Voltage (Max) 19.2 VDC
Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 63.2mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 19.2 VDC
Relay Type General Purpose Coil Type Non Latching Coil Current 63.2mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 19.2 VDC
Coil TypeNon LatchingCoil Current63.2mACoil Voltage24VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage220VDC - MaxTurn On Voltage (Max)19.2 VDC
Coil Current 63.2mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 19.2 VDC
Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 19.2 VDC
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 19.2 VDC
Contact Rating (Current) Switching Voltage 220VDC - Max Turn On Voltage (Max) 19.2 VDC
Switching Voltage 220VDC - Max Turn On Voltage (Max) 19.2 VDC
Turn On Voltage (Max) 19.2 VDC
Turn Off Voltage (Min) 3.6 VDC
•
Operate Time 30ms
Release Time 20ms
Features Test Button
Mounting Type Socketable
Termination Style Plug In
Report errors?

MKS1XTI-10 DC24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MKS1XTI-10 DC24 Payment Methods





















MKS1XTI-10 DC24 Shipping Methods













If you have any question about MKS1XTI-10 DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com