



#### **MKS1XTIN-10 DC24 Information**



For Reference Only

Part Number MKS1XTIN-10 DC24

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 10A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MKS1XTIN-10 DC24 Specifications**

Manufacturer Part Number  Manufacturer  Omron Automation and Safety  Relays  Power Relays, Over 2 Amps  Package  Series  MKS-X  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  63.2mA  Coil Voltage  24VDC  Contact Form  SPST-NO (1 Form A)  Contact Rating (Current)  Switching Voltage  10A  Switching Voltage  19.2 VDC  Turn Off Voltage (Max)  Turn Off Voltage (Min)  Operate Time  30ms  Paleoge Time		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         MKS-X           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         63.2mA           Coil Voltage         24VDC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         10A           Switching Voltage         220VDC - Max           Turn On Voltage (Max)         19.2 VDC           Turn Off Voltage (Min)         3.6 VDC           Operate Time         30ms	Manufacturer Part Number	MKS1XTIN-10 DC24
Package - Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 63.2mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 300ms	Manufacturer	Omron Automation and Safety
Package - MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 63.2mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms	Category	Relays
Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 63.2mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms		Power Relays, Over 2 Amps
Relay Type Coil Type Non Latching Coil Current 63.2mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) Switching Voltage 220VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 30ms	Package	-
Coil Type Non Latching Coil Current 63.2mA Coil Voltage 24VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms	Series	MKS-X
Coil Current 63.2mA  Coil Voltage 24VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 10A  Switching Voltage 220VDC - Max  Turn On Voltage (Max) 19.2 VDC  Turn Off Voltage (Min) 3.6 VDC  Operate Time 30ms	Relay Type	General Purpose
Coil Voltage 24VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 10A  Switching Voltage 220VDC - Max  Turn On Voltage (Max) 19.2 VDC  Turn Off Voltage (Min) 3.6 VDC  Operate Time 30ms	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 10A  Switching Voltage 220VDC - Max  Turn On Voltage (Max) 19.2 VDC  Turn Off Voltage (Min) 3.6 VDC  Operate Time 30ms	Coil Current	63.2mA
Contact Rating (Current)  Switching Voltage  220VDC - Max  Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  3.6 VDC  Operate Time  30ms	Coil Voltage	24VDC
Switching Voltage 220VDC - Max  Turn On Voltage (Max) 19.2 VDC  Turn Off Voltage (Min) 3.6 VDC  Operate Time 30ms	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  3.6 VDC  Operate Time  30ms	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 3.6 VDC 30ms	Switching Voltage	220VDC - Max
Operate Time 30ms	Turn On Voltage (Max)	19.2 VDC
	Turn Off Voltage (Min)	3.6 VDC
Pologoga Timo	Operate Time	30ms
Release Time ZUIIIS	Release Time	20ms
Features LED Indicator, Test Button	Features	LED Indicator, Test Button
Mounting Type Socketable	Mounting Type	Socketable
Termination Style Plug In	Termination Style	Plug In
Report errors?		Report errors?

#### **MKS1XTIN-10 DC24 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **MKS1XTIN-10 DC24 Payment Methods**



















## MKS1XTIN-10 DC24 Shipping Methods













If you have any question about MKS1XTIN-10 DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com