

# **MKS1XTN-10 DC110**

### MKS1XTN-10 DC110 Information

Heisener.com

Part Number MKS1XTN-10 DC110

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 10A 110V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **MKS1XTN-10 DC110 Specifications**

Manufacturer Part NumberMKS1XTN-10 DC110ManufacturerOmron Automation and SafetyCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current13.6mACoil Voltage110VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage220VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesMechanical Indicator		
Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         MKS-X           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         13.6mA           Coil Voltage         110VDC           Contact Form         SPST-NO (1 Form A)           Contact Rating (Current)         10A           Switching Voltage         220VDC - Max           Turn On Voltage (Max)         88 VDC           Turn Off Voltage (Min)         16.5 VDC           Operate Time         30ms           Release Time         20ms	Manufacturer Part Number	MKS1XTN-10 DC110
Package - Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 13.6mA Coil Voltage 110VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 16.5 VDC Operate Time 30ms Release Time 20ms	Manufacturer	Omron Automation and Safety
Package - MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 13.6mA Coil Voltage 110VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 16.5 VDC Operate Time 30ms Release Time 2 20ms	Category	Relays
Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 13.6mA Coil Voltage 110VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 16.5 VDC Operate Time 30ms Release Time 20ms		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 13.6mA  Coil Voltage 110VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 10A  Switching Voltage 220VDC - Max  Turn On Voltage (Max) 88 VDC  Turn Off Voltage (Min) 16.5 VDC  Operate Time 30ms  Release Time 20ms	Package	-
Coil TypeNon LatchingCoil Current13.6mACoil Voltage110VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage220VDC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20ms	Series	MKS-X
Coil Current 13.6mA  Coil Voltage 110VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 10A  Switching Voltage 220VDC - Max  Turn On Voltage (Max) 88 VDC  Turn Off Voltage (Min) 16.5 VDC  Operate Time 30ms  Release Time 20ms	Relay Type	General Purpose
Coil Voltage 110VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 10A  Switching Voltage 220VDC - Max  Turn On Voltage (Max) 88 VDC  Turn Off Voltage (Min) 16.5 VDC  Operate Time 30ms  Release Time 20ms	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 10A  Switching Voltage 220VDC - Max  Turn On Voltage (Max) 88 VDC  Turn Off Voltage (Min) 16.5 VDC  Operate Time 30ms  Release Time 20ms	Coil Current	13.6mA
Contact Rating (Current)  Switching Voltage  220VDC - Max  Turn On Voltage (Max)  88 VDC  Turn Off Voltage (Min)  16.5 VDC  Operate Time  30ms  Release Time  20ms	Coil Voltage	110VDC
Switching Voltage 220VDC - Max Turn On Voltage (Max) 88 VDC Turn Off Voltage (Min) 16.5 VDC Operate Time 30ms Release Time 20ms	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Release Time  88 VDC  16.5 VDC  30ms  20ms	Contact Rating (Current)	10A
Turn Off Voltage (Min)  Operate Time  Release Time  16.5 VDC  30ms  20ms	Switching Voltage	220VDC - Max
Operate Time 30ms Release Time 20ms	Turn On Voltage (Max)	88 VDC
Release Time 20ms	Turn Off Voltage (Min)	16.5 VDC
	Operate Time	30ms
Features Mechanical Indicator	Release Time	20ms
	Features	Mechanical Indicator
Mounting Type Socketable	Mounting Type	Socketable
Termination Style Plug In	Termination Style	Plug In
Report errors?		Report errors?

### MKS1XTN-10 DC110 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MKS1XTN-10 DC110 Payment Methods



















## MKS1XTN-10 DC110 Shipping Methods













If you have any question about MKS1XTN-10 DC110, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com