



MKS1XTN-10 DC48 Information

Heisener.com

Part Number MKS1XTN-10 DC48

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 10A 48V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MKS1XTN-10 DC48 Specifications

Manufacturer MKS1XTN-10 DC48 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 32mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current32mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage220VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)7.2 VDCOperate Time30msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	MKS1XTN-10 DC48
Package - Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 32mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style	Manufacturer	Omron Automation and Safety
Package-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current32mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage220VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)7.2 VDCOperate Time30msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In	Category	Relays
SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current32mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage220VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)7.2 VDCOperate Time30msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 32mA Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current32mACoil Voltage48VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage220VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)7.2 VDCOperate Time30msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In	Series	MKS-X
Coil Current Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 220VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In	Coil Current	32mA
Contact Rating (Current) Switching Voltage 220VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In	Coil Voltage	48VDC
Switching Voltage 220VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 7.2 VDC Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style 38.4 VDC 7.2 VDC Operate Time 30ms Release Time Plug In	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 30ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In	Switching Voltage	220VDC - Max
Operate Time30msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In	Turn On Voltage (Max)	38.4 VDC
Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	7.2 VDC
Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In	Operate Time	30ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	Mechanical Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
100000000000000000000000000000000000000		Report errors?

MKS1XTN-10 DC48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MKS1XTN-10 DC48 Payment Methods



















MKS1XTN-10 DC48 Shipping Methods













If you have any question about MKS1XTN-10 DC48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com