



MKS2T-11 AC100 Information

Heisener.com

Part Number MKS2T-11 AC100

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE DPST 15A 100V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MKS2T-11 AC100 Specifications

Manufacturer Part Number MKS2T-11 AC100 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 23.1mA Coil Voltage 100VAC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPackage-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current23.1mACoil Voltage100VACContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)80 VACTurn Off Voltage (Min)30 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	MKS2T-11 AC100
Package - Series MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 23.1mA Coil Voltage 100VAC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Manufacturer	Omron Automation and Safety
Package - MKS-X Relay Type General Purpose Coil Type Non Latching Coil Current 23.1mA Coil Voltage 100VAC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Purp In Socketable Termination Style	Category	Relays
SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current23.1mACoil Voltage100VACContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)80 VACTurn Off Voltage (Min)30 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Non Latching Coil Type Non Latching Coil Current 23.1mA Coil Voltage 100VAC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current23.1mACoil Voltage100VACContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)80 VACTurn Off Voltage (Min)30 VACOperate Time20msRelease Time20msFeatures-Mounting TypeSocketableTermination StylePlug In	Series	MKS-X
Coil Current Coil Voltage 100VAC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style	Relay Type	General Purpose
Coil Voltage 100VAC Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form DPST-NO/NC (1 Form A and B) Contact Rating (Current) 15A Switching Voltage 250VAC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Coil Current	23.1mA
Contact Rating (Current) Switching Voltage 250VAC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style	Coil Voltage	100VAC
Switching Voltage 250VAC - Max Turn On Voltage (Max) 80 VAC Turn Off Voltage (Min) 30 VAC Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Contact Form	DPST-NO/NC (1 Form A and B)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style 80 VAC 20ms 20ms 20ms Plug In	Contact Rating (Current)	15A
Turn Off Voltage (Min) Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style 30 VAC 20ms Found Plug In	Switching Voltage	250VAC - Max
Operate Time 20ms Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	80 VAC
Release Time 20ms Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	30 VAC
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In	Release Time	20ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

MKS2T-11 AC100 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MKS2T-11 AC100 Payment Methods



















MKS2T-11 AC100 Shipping Methods













If you have any question about MKS2T-11 AC100, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com