

MKS2TI-11 DC110

MKS2TI-11 DC110 Information

Heisener.com	 MKS2TI-11 DC110 Omron Automation and Safety Relays Power Relays, Over 2 Amps RELAY GEN PURPOSE DPST 15A 110V - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKS2TI-11 DC110 Specifications

ManufacturerOmron Automation and SafetyCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current13.6mACoil Voltage110VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)15ASwitching Voltage20VAC - MaxTurn On Voltage (Max)88 VDCTurn On Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In		
CategoryRelaysPackage-Package-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current13.6mACoil Voltage110VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time20msRelease Time20msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	MKS2TI-11 DC110
Power Relays, Over 2 AmpsPackage-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current13.6mACoil Voltage110VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package-SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current13.6mACoil Voltage110VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesTest ButtonMounting TypeSocketableTermination StylePug In	Category	Relays
SeriesMKS-XRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current13.6mACoil Voltage110VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current13.6mACoil Voltage110VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesTest ButtonMounting TypeSocketableTermination StylePug In	Package	-
Coil TypeNon LatchingCoil Current13.6mACoil Voltage110VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In	Series	MKS-X
Coil Current13.6mACoil Voltage110VDCContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Contact FormInformationContact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In	Coil Type	Non Latching
Contact FormDPST-NO/NC (1 Form A and B)Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In	Coil Current	13.6mA
Contact Rating (Current)15ASwitching Voltage250VAC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In	Coil Voltage	110VDC
Switching Voltage250VAC - MaxTurn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In	Contact Form	DPST-NO/NC (1 Form A and B)
Turn On Voltage (Max)88 VDCTurn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In	Contact Rating (Current)	15A
Turn Off Voltage (Min)16.5 VDCOperate Time30msRelease Time20msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In	Switching Voltage	250VAC - Max
Operate Time30msRelease Time20msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In	Turn On Voltage (Max)	88 VDC
Release Time20msFeaturesTest ButtonMounting TypeSocketableTermination StylePlug In	Turn Off Voltage (Min)	16.5 VDC
FeaturesTest ButtonMounting TypeSocketableTermination StylePlug In	Operate Time	30ms
Mounting TypeSocketableTermination StylePlug In	Release Time	20ms
Termination Style Plug In	Features	Test Button
· · ·	Mounting Type	Socketable
	Termination Style	Plug In
Report errors?		Report errors?

MKS2TI-11 DC110 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MKS2TI-11 DC110 Payment Methods



MKS2TI-11 DC110 Shipping Methods



If you have any question about MKS2TI-11 DC110, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com