

### MKS3P-2 AC240 Information

Heisener.com

Part Number MKS3P-2 AC240

Manufacturer Omron Automation and Safety

**Category** Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 3PDT 10A 240V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## MKS3P-2 AC240 Specifications

Manufacturer Part Number         MKS3P-2 AC240           Manufacturer         Omron Automation and Safety           Category         Relays           Power Relays, Over 2 Amps           Package         -           Series         MKS           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         9.6mA           Coil Voltage         240VAC           Contact Form         3PDT (3 Form C)           Contact Rating (Current)         10A           Switching Voltage         250VAC, 30VDC - Max           Turn On Voltage (Max)         192 VAC           Turn Off Voltage (Min)         72 VAC           Operate Time         20ms           Release Time         20ms           Features         Mechanical Indicator           Mounting Type         Socketable           Termination Style         Plug In, 11 Pin (Octal)		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesMKSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.6mACoil Voltage240VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Manufacturer Part Number	MKS3P-2 AC240
Package-SeriesMKSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.6mACoil Voltage240VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Manufacturer	Omron Automation and Safety
Package-SeriesMKSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.6mACoil Voltage240VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Category	Relays
SeriesMKSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current9.6mACoil Voltage240 V ACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250 V AC, 30 V DC - MaxTurn On Voltage (Max)192 V ACTurn Off Voltage (Min)72 V ACOperate Time20msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 9.6mA Coil Voltage 240VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Package	-
Coil TypeNon LatchingCoil Current9.6mACoil Voltage240VACContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)192 VACTurn Off Voltage (Min)72 VACOperate Time20msRelease Time20msFeaturesMechanical IndicatorMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Series	MKS
Coil Current Coil Voltage 240VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Relay Type	General Purpose
Coil Voltage 240VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 192 VAC Turn Off Voltage (Min) 72 VAC Operate Time 20ms Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Type	Non Latching
Contact Form 3PDT (3 Form C)  Contact Rating (Current) 10A  Switching Voltage 250VAC, 30VDC - Max  Turn On Voltage (Max) 192 VAC  Turn Off Voltage (Min) 72 VAC  Operate Time 20ms  Release Time 20ms  Release Time 20ms  Features Mechanical Indicator  Mounting Type Socketable  Termination Style Plug In, 11 Pin (Octal)	Coil Current	9.6mA
Contact Rating (Current)  Switching Voltage  250VAC, 30VDC - Max  Turn On Voltage (Max)  192 VAC  Turn Off Voltage (Min)  72 VAC  Operate Time  20ms  Release Time  20ms  Features  Mechanical Indicator  Mounting Type  Socketable  Termination Style  Plug In, 11 Pin (Octal)	Coil Voltage	240VAC
Switching Voltage 250VAC, 30VDC - Max  Turn On Voltage (Max) 192 VAC  Turn Off Voltage (Min) 72 VAC  Operate Time 20ms  Release Time 20ms  Features Mechanical Indicator  Mounting Type Socketable  Termination Style Plug In, 11 Pin (Octal)	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max)  192 VAC  Turn Off Voltage (Min)  72 VAC  Operate Time  20ms  Release Time  20ms  Features  Mechanical Indicator  Mounting Type  Socketable  Termination Style  Plug In, 11 Pin (Octal)	Contact Rating (Current)	10A
Turn Off Voltage (Min)  72 VAC  Operate Time  20ms  Release Time  20ms  Features  Mechanical Indicator  Mounting Type  Socketable  Termination Style  Plug In, 11 Pin (Octal)	Switching Voltage	250VAC, 30VDC - Max
Operate Time 20ms  Release Time 20ms  Features Mechanical Indicator  Mounting Type Socketable  Termination Style Plug In, 11 Pin (Octal)	Turn On Voltage (Max)	192 VAC
Release Time 20ms Features Mechanical Indicator Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Turn Off Voltage (Min)	72 VAC
Features Mechanical Indicator  Mounting Type Socketable  Termination Style Plug In, 11 Pin (Octal)	Operate Time	20ms
Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Release Time	20ms
Termination Style Plug In, 11 Pin (Octal)	Features	Mechanical Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, 11 Pin (Octal)
		Report errors?

#### MKS3P-2 AC240 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# MKS3P-2 AC240 Payment Methods





















### MKS3P-2 AC240 Shipping Methods













If you have any question about MKS3P-2 AC240, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com