



### MKS3P-5 AC110 Information



For Reference Only

Part Number MKS3P-5 AC110

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE 3PDT 10A 110V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## MKS3P-5 AC110 Specifications

Manufacturer Part Number  Manufacturer  Omron Automation and Safety  Relays  Power Relays, Over 2 Amps  Package  Series  MKS  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  Coil Voltage  Contact Form  3PDT (3 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 30VDC - Max
Category  Relays  Power Relays, Over 2 Amps  Package  Series  MKS  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  21mA  Coil Voltage  110VAC  Contact Form  3PDT (3 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 30VDC - Max
Package Series MKS Relay Type General Purpose Coil Type Non Latching Coil Current 21mA Coil Voltage 110VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max
Package - Series MKS Relay Type General Purpose Coil Type Non Latching Coil Current 21mA Coil Voltage 110VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max
Series MKS  Relay Type General Purpose  Coil Type Non Latching  Coil Current 21mA  Coil Voltage 110VAC  Contact Form 3PDT (3 Form C)  Contact Rating (Current) 10A  Switching Voltage 250VAC, 30VDC - Max
Relay Type  Coil Type  Non Latching  Coil Current  21mA  Coil Voltage  110VAC  Contact Form  3PDT (3 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 30VDC - Max
Coil Type  Non Latching  Coil Current  21mA  Coil Voltage  110VAC  Contact Form  3PDT (3 Form C)  Contact Rating (Current)  10A  Switching Voltage  250VAC, 30VDC - Max
Coil Current 21mA  Coil Voltage 110VAC  Contact Form 3PDT (3 Form C)  Contact Rating (Current) 10A  Switching Voltage 250VAC, 30VDC - Max
Coil Voltage 110VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max
Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max
Contact Rating (Current)  Switching Voltage  10A  250VAC, 30VDC - Max
Switching Voltage 250VAC, 30VDC - Max
T 0 11 1 01 1
Turn On Voltage (Max) 88 VAC
Turn Off Voltage (Min) 33 VAC
Operate Time 20ms
Release Time 20ms
Features Mechanical Indicator
Mounting Type Socketable
Termination Style Plug In, 11 Pin (Octal)
Report errors

#### MKS3P-5 AC110 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## MKS3P-5 AC110 Payment Methods





















### **MKS3P-5 AC110 Shipping Methods**













If you have any question about MKS3P-5 AC110, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com