



MKS3P-5 AC110 Information



For Reference Only

Part Number MKS3P-5 AC110

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 3PDT 10A 110V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MKS3P-5 AC110 Specifications

Manufacturer Part Number Manufacturer Omron Automation and Safety Relays Power Relays, Over 2 Amps Package Series MKS Relay Type General Purpose Coil Type Non Latching Coil Current Coil Voltage Contact Form 3PDT (3 Form C) Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max
Category Relays Power Relays, Over 2 Amps Package Series MKS Relay Type General Purpose Coil Type Non Latching Coil Current 21mA Coil Voltage 110VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max
Package Series MKS Relay Type General Purpose Coil Type Non Latching Coil Current 21mA Coil Voltage 110VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max
Package - Series MKS Relay Type General Purpose Coil Type Non Latching Coil Current 21mA Coil Voltage 110VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max
Series MKS Relay Type General Purpose Coil Type Non Latching Coil Current 21mA Coil Voltage 110VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max
Relay Type Coil Type Non Latching Coil Current 21mA Coil Voltage 110VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max
Coil Type Non Latching Coil Current 21mA Coil Voltage 110VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max
Coil Current 21mA Coil Voltage 110VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max
Coil Voltage 110VAC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max
Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max
Contact Rating (Current) Switching Voltage 10A 250VAC, 30VDC - Max
Switching Voltage 250VAC, 30VDC - Max
T 0 11 1 01 1
Turn On Voltage (Max) 88 VAC
Turn Off Voltage (Min) 33 VAC
Operate Time 20ms
Release Time 20ms
Features Mechanical Indicator
Mounting Type Socketable
Termination Style Plug In, 11 Pin (Octal)
Report errors

MKS3P-5 AC110 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MKS3P-5 AC110 Payment Methods





















MKS3P-5 AC110 Shipping Methods













If you have any question about MKS3P-5 AC110, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com