



MKS3PI1-D-5 DC24 Information

Heisener.com

Part Number MKS3PI1-D-5 DC24

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 3PDT 10A 24V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MKS3PI1-D-5 DC24 Specifications

Manufacturer Part Number MKS3PI1-D-5 DC24 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series MKS Relay Type General Purpose Coil Type Non Latching Coil Current 55.8mA Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms Release Time 40ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)		
Category Relays Power Relays, Over 2 Amps Package Series MKS Relay Type General Purpose Coil Type Non Latching Coil Current 55.8mA Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms Release Time 40ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Manufacturer Part Number	MKS3PI1-D-5 DC24
Package-SeriesMKSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current55.8mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)3.6 VDCOperate Time30msRelease Time40msFeaturesDiode, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Manufacturer	Omron Automation and Safety
Package-SeriesMKSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current55.8mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)3.6 VDCOperate Time30msRelease Time40msFeaturesDiode, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Category	Relays
SeriesMKSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current55.8mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)3.6 VDCOperate Time30msRelease Time40msFeaturesDiode, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 55.8mA Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms Release Time 40ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Package	-
Coil TypeNon LatchingCoil Current55.8mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 30VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)3.6 VDCOperate Time30msRelease Time40msFeaturesDiode, Mechanical Indicator, Test ButtonMounting TypeSocketableTermination StylePlug In, 11 Pin (Octal)	Series	MKS
Coil Current Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms Release Time 40ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms Release Time 40ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Type	Non Latching
Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms Release Time 40ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Current	55.8mA
Contact Rating (Current) Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms Release Time 40ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Coil Voltage	24VDC
Switching Voltage 250VAC, 30VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms Release Time 40ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 30ms Release Time 40ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 30ms Release Time 40ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Switching Voltage	250VAC, 30VDC - Max
Operate Time 30ms Release Time 40ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Turn On Voltage (Max)	19.2 VDC
Release Time 40ms Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Turn Off Voltage (Min)	3.6 VDC
Features Diode, Mechanical Indicator, Test Button Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Operate Time	30ms
Mounting Type Socketable Termination Style Plug In, 11 Pin (Octal)	Release Time	40ms
Termination Style Plug In, 11 Pin (Octal)	Features	Diode, Mechanical Indicator, Test Button
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, 11 Pin (Octal)
		Report errors?

MKS3PI1-D-5 DC24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MKS3PI1-D-5 DC24 Payment Methods



















MKS3PI1-D-5 DC24 Shipping Methods













If you have any question about MKS3PI1-D-5 DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com