

MKT1813522015

MKT1813522015 Information

Heisener.com	ner.com		MKT1813522015 Vishay BC Components Capacitors Film Capacitors CAP FILM 2.2UF 10% 100VDC AXIAL Axial For the pricing/inventory/lead time, please contact	
For Referer	Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKT1813522015 Specifications

Manufacturer Part NumberMKT1813522015ManufacturerVishay BC ComponentsCategoryCapacitorsPackageAxialPackageAxialSeriesMKT1813Capacitance2.2µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, MetallizedSR (Equivalent Series Resistance)-Operating Temperature-S5°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.374° Di ax 1.043° L (9.50mm x 26.50mm)Height - Seated (Max)-Lead Spacing-ApplicationsGeneral PurposeFerminationGeneral Purpose		
CategoryCapacitorsFiln CapacitorsPackageAxialSoriesMKT1813Capacitance2.2µFYoltage Rating - AC63VVoltage Rating - AC00VDielectric MaterialPolyester, MetallizedDielectric Material-Youting Type-55°C - 100°CMounting Type-55°C - 100°CPackage / Case-374° Dia r.1.043° L (9.50mm x 26.50mm)Fight - Seated (Max)-Height - Seated (Max)-Lead Spacing-Features-Features-Features-Applications-Features-	Manufacturer Part Number	MKT1813522015
Fin CapacitorsPackageAxialSeriesMKT1813Capacitance2.2µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialKize / Dimension0.374" Dia x 1.043" L (9.50mm x 26.50mm)Height - Seated (Max)-Lead Spacing-ApplicationsGeneral PurposeFeatures-Features-	Manufacturer	Vishay BC Components
PackageAxialSeriesMKT1813Capacitance2.2µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, MetallizedDielectric Material-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.374" Dia x 1.043" L (9.50mm x 26.50mm)Height - Seated (Max)-Lead Spacing-ApplicationsGeneral PurposeFeatures-Features-	Category	Capacitors
SeriesMKT1813Capacitance2.2µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, MetallizedDielectric Material-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.374" Dia x 1.043" L (9.50mm x 26.50mm)Height - Seated (Max)-Lead Spacing-ApplicationsGeneral PurposeFeatures-Features-		Film Capacitors
Capacitance2.2µFTolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, MetallizedDielectric Material-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.374" Dia x 1.043" L (9.50mm x 26.50mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package	Axial
Tolerance±10%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.374" Dia x 1.043" L (9.50mm x 26.50mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-ApplicationsGeneral PurposeFeatures-	Series	MKT1813
Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.374" Dia x 1.043" L (9.50mm x 26.50mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-ApplicationsGeneral PurposeFeatures-	Capacitance	2.2µF
Voltage Rating - DC100VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.374" Dia x 1.043" L (9.50mm x 26.50mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-ApplicationsGeneral PurposeFeatures-	Tolerance	±10%
Dielectric MaterialPolyester, MetallizedDielectric Material-ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.374" Dia x 1.043" L (9.50mm x 26.50mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	63V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.374" Dia x 1.043" L (9.50mm x 26.50mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	100V
Operating Temperature-55°C ~ 100°CMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.374" Dia x 1.043" L (9.50mm x 26.50mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyester, Metallized
Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.374" Dia x 1.043" L (9.50mm x 26.50mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseAxialSize / Dimension0.374" Dia x 1.043" L (9.50mm x 26.50mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 100°C
Size / Dimension0.374" Dia x 1.043" L (9.50mm x 26.50mm)Height - Seated (Max)-TerminationPC PinsLead Spacing-ApplicationsGeneral PurposeFeatures-	Mounting Type	Through Hole
Height - Seated (Max)-TerminationPC PinsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package / Case	Axial
TerminationPC PinsLead Spacing-ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.374" Dia x 1.043" L (9.50mm x 26.50mm)
Lead Spacing-ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	-
ApplicationsGeneral PurposeFeatures-	Termination	PC Pins
Features -	Lead Spacing	-
	Applications	General Purpose
Deventering	Features	-
Report errors		Report errors?

MKT1813522015 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MKT1813522015 Payment Methods



MKT1813522015 Shipping Methods



If you have any question about MKT1813522015, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com