

MKT1817433016

MKT1817433016 Information

Contact and they	Part Number Manufacturer Category Description Package	MKT1817433016 Vishay BC Components Capacitors Film Capacitors CAP FILM 0.33UF 20% 100VDC RAD Radial For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MKT1817433016 Specifications

ManufacturerVishay BC ComponentsCategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesMKT1817Capacitance0.33µFTolerance±20%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, MetallizedStyre Figure Rating - Styre Resistance)-Operating Temperature-55°C ~ 105°CNounting TypeRadialSize / Dimension0.283°L x 0.177° W (7.20mm x 4.50mm)Height - Seated (Max)0.354″ (9.00mm)TerminationPC PinsLead Spacing0.197° (5.00mm)Features5.000000000000000000000000000000000000		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesMKT1817Capacitance0.33µFTolerance±20%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, MetallizedSeries Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Manufacturer Part Number	MKT1817433016
Film CapacitorsPackageRadialSeriesMKT1817Capacitance0.33µFTolerance±20%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)Lead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Manufacturer	Vishay BC Components
PackageRadialSeriesMKT1817Capacitance0.33µFTolerance±20%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Category	Capacitors
Series MKT1817 Capacitance 0.33µF Tolerance ±20% Voltage Rating - AC 63V Voltage Rating - DC 100V Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.283°L x 0.177" W (7.20mm x 4.50mm) Height - Seated (Max) 0.354" (9.00mm) Lead Spacing 0.197" (5.00mm) Applications General Purpose Features -		Film Capacitors
Capacitance0.33µFCopacitance±20%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.354" (9.00mm) 4.50mm)Height - Seated (Max)0.354" (9.00mm)Lead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Package	Radial
Tolerance±20%Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing6.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Series	MKT1817
Voltage Rating - AC63VVoltage Rating - DC100VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Capacitance	0.33µF
Voltage Rating - DC100VDielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Tolerance	±20%
Dielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	63V
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	100V
Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyester, Metallized
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 105°C
Size / Dimension0.283" L x 0.177" W (7.20mm x 4.50mm)Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.354" (9.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.283" L x 0.177" W (7.20mm x 4.50mm)
Lead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.354" (9.00mm)
ApplicationsGeneral PurposeFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.197" (5.00mm)
	Applications	General Purpose
Report errors?	Features	-
		Report errors?

MKT1817433016 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MKT1817433016 Payment Methods



MKT1817433016 Shipping Methods



If you have any question about MKT1817433016, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com