



MLH004BGB01B Information



For Reference Only

Part Number MLH004BGB01B

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR GAUGE 0-4 BAR

Package Cylinder, Metal

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MI HOMBCROIR	Specifications
MLH004BGB01B	Specifications

Manufacturer Part Number MLH004BGB01B Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package Cylinder, Metal Series MLH Pressure Type Vented Gauge Operating Pressure 58.02 PSI (400 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±05% Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 174.05 PSI (1200 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package - Report errors?			
CategorySensors, TransducersPackageCylinder, MetalSeriesMLHPressure TypeVented GaugeOperating Pressure58.02 PSI (400 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±05%Voltage - Supply9.5 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard Metripak 150Maximum Pressure174.05 PSI (1200 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Manufacturer Part Number	MLH004BGB01B	
Package Cylinder, Metal Series MLH Pressure Type Vented Gauge Operating Pressure S8.02 PSI (400 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±05% Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 174.05 PSI (1200 kPa) Operating Temperature - 40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions	
PackageCylinder, MetalSeriesMLHPressure TypeVented GaugeOperating Pressure58.02 PSI (400 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±05%Voltage - Supply9.5 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard Metripak 150Maximum Pressure174.05 PSI (1200 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Category	Sensors, Transducers	
SeriesMLHPressure TypeVented GaugeOperating Pressure58.02 PSI (400 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±05%Voltage - Supply9.5 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard Metripak 150Maximum Pressure174.05 PSI (1200 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-		Pressure Sensors, Transducers	
Pressure Type Vented Gauge Operating Pressure 58.02 PSI (400 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±05% Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 174.05 PSI (1200 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Package	Cylinder, Metal	
Operating Pressure 58.02 PSI (400 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±05% Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 174.05 PSI (1200 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Series	MLH	
Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±05%Voltage - Supply9.5 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard Metripak 150Maximum Pressure174.05 PSI (1200 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Pressure Type	Vented Gauge	
Output 4 mA ~ 20 mA Accuracy ±05% Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 174.05 PSI (1200 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Operating Pressure	58.02 PSI (400 kPa)	
Accuracy ±05% Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 174.05 PSI (1200 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Output Type	Analog Current	
Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 174.05 PSI (1200 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Output	4 mA ~ 20 mA	
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 174.05 PSI (1200 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Accuracy	±05%	
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 174.05 PSI (1200 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Voltage - Supply	9.5 V ~ 30 V	
Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 174.05 PSI (1200 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Port Size	Male - 1/4" (6.35mm) NPT	
Termination Style Packard Metripak 150 Maximum Pressure 174.05 PSI (1200 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Style	Threaded	
Maximum Pressure174.05 PSI (1200 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Features	Amplified Output, Temperature Compensated	
Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Termination Style	Packard Metripak 150	
Package / Case Cylinder, Metal Supplier Device Package -	Maximum Pressure	174.05 PSI (1200 kPa)	
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C	
	Package / Case	Cylinder, Metal	
Report errors?	Supplier Device Package	-	
			Report errors?

MLH004BGB01B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MLH004BGB01B Payment Methods



















MLH004BGB01B Shipping Methods













If you have any question about MLH004BGB01B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com