



MLH010BSB06E Information

Heisener.com

Part Number MLH010BSB06E

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR GAUGE 0-10 BAR

Package Cylinder, Metal

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MLH010BSB06E Specifications

Manufacturer Part Number MLH010BSB06E Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package Cylinder, Metal Series MLH Pressure Type Sealed Gauge Operating Pressure 145.04 PSI (1000 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 7 V ~ 30 V Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 435.11 PSI (3000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package - Report errors?		
CategorySensors, TransducersPackageCylinder, MetalSeriesMLHPressure TypeSealed GaugeOperating Pressure145.04 PSI (1000 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply7 V ~ 30 VPort SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard Metripak 150Maximum Pressure435.11 PSI (3000 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Manufacturer Part Number	MLH010BSB06E
Package Cylinder, Metal Series MLH Pressure Type Sealed Gauge Operating Pressure 145.04 PSI (1000 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 7 V ~ 30 V Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 435.11 PSI (3000 kPa) Operating Temperature - 40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions
PackageCylinder, MetalSeriesMLHPressure TypeSealed GaugeOperating Pressure145.04 PSI (1000 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply7 V ~ 30 VPort SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard Metripak 150Maximum Pressure435.11 PSI (3000 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Category	Sensors, Transducers
SeriesMLHPressure TypeSealed GaugeOperating Pressure145.04 PSI (1000 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply7 V ~ 30 VPort SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard Metripak 150Maximum Pressure435.11 PSI (3000 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Operating Pressure 145.04 PSI (1000 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 7 V ~ 30 V Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 435.11 PSI (3000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Package	Cylinder, Metal
Operating Pressure 145.04 PSI (1000 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 7 V ~ 30 V Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 435.11 PSI (3000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Series	MLH
Output Type	Pressure Type	Sealed Gauge
Output $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $7 \text{ V} \sim 30 \text{ V}$ Port Size $\text{Male - 1/8" (3.18mm) NPT}$ Port Style Threaded Features $\text{Amplified Output, Temperature Compensated}$ Termination Style $\text{Packard Metripak 150}$ Maximum Pressure $435.11 \text{ PSI (3000 kPa)}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case Cylinder, Metal Supplier Device Package $-$	Operating Pressure	145.04 PSI (1000 kPa)
Accuracy ±0.25% Voltage - Supply 7 V ~ 30 V Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 435.11 PSI (3000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Output Type	Analog Voltage
Voltage - Supply Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 435.11 PSI (3000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Output	0.5 V ~ 4.5 V
Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 435.11 PSI (3000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Accuracy	±0.25%
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 435.11 PSI (3000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Voltage - Supply	7 V ~ 30 V
Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 435.11 PSI (3000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Size	Male - 1/8" (3.18mm) NPT
Termination Style Packard Metripak 150 Maximum Pressure 435.11 PSI (3000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Style	Threaded
Maximum Pressure 435.11 PSI (3000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Features	Amplified Output, Temperature Compensated
Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Termination Style	Packard Metripak 150
Package / Case Cylinder, Metal Supplier Device Package -	Maximum Pressure	435.11 PSI (3000 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	Cylinder, Metal
Report errors?	Supplier Device Package	-
		Report errors?

MLH010BSB06E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MLH010BSB06E Payment Methods





















MLH010BSB06E Shipping Methods













If you have any question about MLH010BSB06E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com