



MLH050PGT01B Information

Heisener.com

Part Number MLH050PGT01B

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description MLH ALL METAL PRESS SENSE -ATF

Package Cylinder, Metal

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MLH050PGT01B Specifications

Manufacturer Part Number MLH050PGT01B Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package Cylinder, Metal Series MLH Pressure Type Vented Gauge Operating Pressure 50 PSI (344.74 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 150 PSI (1034.21 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package - Report errors?			
CategorySensors, TransducersPackageCylinder, MetalSeriesMLHPressure TypeVented GaugeOperating Pressure50 PSI (344.74 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9.5 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure150 PSI (1034.21 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Manufacturer Part Number	MLH050PGT01B	
Package Cylinder, Metal Series MLH Pressure Type Vented Gauge Operating Pressure Operating Pressure Analog Current Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure 150 PSI (1034.21 kPa) Operating Temperature - 40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions	
PackageCylinder, MetalSeriesMLHPressure TypeVented GaugeOperating Pressure50 PSI (344.74 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9.5 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure150 PSI (1034.21 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Category	Sensors, Transducers	
SeriesMLHPressure TypeVented GaugeOperating Pressure50 PSI (344.74 kPa)Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9.5 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure150 PSI (1034.21 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-		Pressure Sensors, Transducers	
Pressure Type Vented Gauge Operating Pressure 50 PSI (344.74 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 150 PSI (1034.21 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Package	Cylinder, Metal	
Operating Pressure 50 PSI (344.74 kPa) Output Type Analog Current Output 4 mA ~ 20 mA Accuracy ±0.25% Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 150 PSI (1034.21 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Series	MLH	
Output TypeAnalog CurrentOutput4 mA ~ 20 mAAccuracy±0.25%Voltage - Supply9.5 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure150 PSI (1034.21 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Pressure Type	Vented Gauge	
Output $4 \text{ mA} \sim 20 \text{ mA}$ Accuracy $\pm 0.25\%$ Voltage - Supply $9.5 \text{ V} \sim 30 \text{ V}$ Port Size $Male - 1/4"$ (6.35mm) NPT Port Style $Threaded$ Features $Amplified Output, Temperature Compensated$ Termination Style $-$ Maximum Pressure $150 \text{ PSI } (1034.21 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / Case $Cylinder, Metal$ Supplier Device Package $-$	Operating Pressure	50 PSI (344.74 kPa)	
Accuracy ±0.25% Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 150 PSI (1034.21 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Output Type	Analog Current	
Voltage - Supply 9.5 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 150 PSI (1034.21 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Output	4 mA ~ 20 mA	
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 150 PSI (1034.21 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Accuracy	±0.25%	
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 150 PSI (1034.21 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Voltage - Supply	9.5 V ~ 30 V	
Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 150 PSI (1034.21 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) NPT	
Termination Style - Maximum Pressure 150 PSI (1034.21 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Style	Threaded	
Maximum Pressure150 PSI (1034.21 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Features	Amplified Output, Temperature Compensated	
Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Termination Style	-	
Package / Case Cylinder, Metal Supplier Device Package -	Maximum Pressure	150 PSI (1034.21 kPa)	
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C	
	Package / Case	Cylinder, Metal	
Report errors?	Supplier Device Package	-	
			Report errors?

MLH050PGT01B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MLH050PGT01B Payment Methods





















MLH050PGT01B Shipping Methods













If you have any question about MLH050PGT01B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com