



MLH05KPSP01E Information

Heisener.com

Part Number MLH05KPSP01E

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description MLH ALL METAL PRESS SENSE -ATF

Package Cylinder, Metal

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MLH05KPSP01E Specifications

Manufacturer Part Number MLH05KPSP01E Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package Cylinder, Metal Series MLH Pressure Type Sealed Gauge Operating Pressure 5000 PSI (34473.79 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 7 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 7500 PSI (51710.68 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package - Report errors? Report errors?			
Category Sensors, Transducers Package Cylinder, Metal Series MLH Pressure Type Sealed Gauge Operating Pressure 5000 PSI (34473.79 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 7 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 7500 PSI (51710.68 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Manufacturer Part Number	MLH05KPSP01E	
Package Cylinder, Metal Series MLH Pressure Type Sealed Gauge Operating Pressure 5000 PSI (34473.79 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 7 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 7500 PSI (51710.68 kPa) Operating Temperature - 40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions	
PackageCylinder, MetalSeriesMLHPressure TypeSealed GaugeOperating Pressure5000 PSI (34473.79 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply7 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure7500 PSI (51710.68 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Category	Sensors, Transducers	
SeriesMLHPressure TypeSealed GaugeOperating Pressure5000 PSI (34473.79 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply7 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure7500 PSI (51710.68 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-		Pressure Sensors, Transducers	
Pressure TypeSealed GaugeOperating Pressure5000 PSI (34473.79 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply7 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure7500 PSI (51710.68 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Package	Cylinder, Metal	
Operating Pressure 5000 PSI (34473.79 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 7 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style	Series	MLH	
Output TypeAnalog VoltageOutput $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $7 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $1/4$ " (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure $7500 \text{ PSI } (51710.68 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinder, MetalSupplier Device Package-	Pressure Type	Sealed Gauge	
Output 0.5 V \sim 4.5 V Accuracy \pm 0.25% Voltage - Supply 7 V \sim 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 7500 PSI (51710.68 kPa) Operating Temperature -40°C \sim 125°C Package / Case Cylinder, Metal Supplier Device Package -	Operating Pressure	5000 PSI (34473.79 kPa)	
Accuracy ±0.25% Voltage - Supply 7 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 7500 PSI (51710.68 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Output Type	Analog Voltage	
Voltage - Supply 7 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 7500 PSI (51710.68 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Output	0.5 V ~ 4.5 V	
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 7500 PSI (51710.68 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Accuracy	±0.25%	
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 7500 PSI (51710.68 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Voltage - Supply	7 V ~ 30 V	
Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 7500 PSI (51710.68 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) NPT	
Termination Style - Maximum Pressure 7500 PSI (51710.68 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Style	Threaded	
Maximum Pressure7500 PSI (51710.68 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Features	Amplified Output, Temperature Compensated	
Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Termination Style	-	
Package / Case Cylinder, Metal Supplier Device Package -	Maximum Pressure	7500 PSI (51710.68 kPa)	
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C	
	Package / Case	Cylinder, Metal	
Report errors?	Supplier Device Package	-	
			Report errors?

MLH05KPSP01E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MLH05KPSP01E Payment Methods





















MLH05KPSP01E Shipping Methods













If you have any question about MLH05KPSP01E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com