



## **MLH05KPST10A Information**

Heisener.com

Part Number MLH05KPST10A

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

**Description** MLH ALL METAL PRESS SENSE -ATF

**Package** Cylinder, Metal

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MLH05KPST10A Specifications**

Manufacturer Part NumberMLH05KPST10AManufacturerHoneywell Sensing and Productivity SolutionsCategorySensors, TransducersPackageCylinder, MetalSeriesMLHPressure TypeSealed GaugeOperating Pressure5000 PSI (34473.79 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature Compensated
CategorySensors, TransducersPackageCylinder, MetalSeriesMLHPressure TypeSealed GaugeOperating Pressure5000 PSI (34473.79 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature Compensated
Pressure Sensors, Transducers  Package Cylinder, Metal  Series MLH  Pressure Type Sealed Gauge  Operating Pressure 5000 PSI (34473.79 kPa)  Output Type Analog Voltage  Output Quit Under Supply 5 V ~ 4.5 V  Accuracy ±0.25%  Voltage - Supply 5 V ~ 6 V  Port Size Male - 7/16" (11.11mm) UNF  Port Style Threaded  Features Amplified Output, Temperature Compensated
PackageCylinder, MetalSeriesMLHPressure TypeSealed GaugeOperating Pressure5000 PSI (34473.79 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature Compensated
SeriesMLHPressure TypeSealed GaugeOperating Pressure $5000 \text{ PSI } (34473.79 \text{ kPa})$ Output TypeAnalog VoltageOutput $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $5 \text{ V} \sim 6 \text{ V}$ Port SizeMale - $7/16$ " (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature Compensated
Pressure TypeSealed GaugeOperating Pressure $5000 \text{ PSI } (34473.79 \text{ kPa})$ Output TypeAnalog VoltageOutput $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $5 \text{ V} \sim 6 \text{ V}$ Port SizeMale - $7/16$ " (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature Compensated
Operating Pressure $5000 \text{ PSI } (34473.79 \text{ kPa})$ Output TypeAnalog VoltageOutput $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $5 \text{ V} \sim 6 \text{ V}$ Port SizeMale - $7/16$ " (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature Compensated
Output TypeAnalog VoltageOutput $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $5 \text{ V} \sim 6 \text{ V}$ Port SizeMale - $7/16$ " (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature Compensated
Output $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $5 \text{ V} \sim 6 \text{ V}$ Port Size $\text{Male - 7/16" (11.11mm) UNF}$ Port Style $\text{Threaded}$ Features $\text{Amplified Output, Temperature Compensated}$
Accuracy $\pm 0.25\%$ Voltage - Supply $5 \text{ V} \sim 6 \text{ V}$ Port Size $\text{Male - 7/16" (11.11mm) UNF}$ Port Style $\text{Threaded}$ Features $\text{Amplified Output, Temperature Compensated}$
Voltage - Supply $5 \text{ V} \sim 6 \text{ V}$ Port Size $Male - 7/16'' (11.11 \text{mm}) \text{ UNF}$ Port Style $Threaded$ Features $Amplified Output, Temperature Compensated$
Port Size Male - 7/16" (11.11mm) UNF  Port Style Threaded  Features Amplified Output, Temperature Compensated
Port Style Threaded Features Amplified Output, Temperature Compensated
Features Amplified Output, Temperature Compensated
1 1 1 1
Termination Style -
Maximum Pressure 7500 PSI (51710.68 kPa)
Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$
Package / Case Cylinder, Metal
Supplier Device Package -
Report errors's

### **MLH05KPST10A Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **MLH05KPST10A Payment Methods**



















## MLH05KPST10A Shipping Methods













If you have any question about MLH05KPST10A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com