



MLH08KPST03A Information

Heisener.com

Part Number MLH08KPST03A

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description MLH ALL METAL PRESS SENSE -ATF

Package Cylinder, Metal

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MLH08KPST03A Specifications

Manufacturer Part Number MLH08KPST03A Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package Cylinder, Metal Series MLH Pressure Type Sealed Gauge Operating Pressure 8000 PSI (55158.06 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 5 V ~ 6 V Port Size Male - M14 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 12000 PSI (82737.09 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package - Report errors?		
CategorySensors, TransducersPackageCylinder, MetalSeriesMLHPressure TypeSealed GaugeOperating Pressure8000 PSI (55158.06 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - M14 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure12000 PSI (82737.09 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Manufacturer Part Number	MLH08KPST03A
Package Cylinder, Metal Series MLH Pressure Type Sealed Gauge Operating Pressure Output Type Analog Voltage Output Outout Utpue O.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 5 V ~ 6 V Port Size Male - M14 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Amaximum Pressure 12000 PSI (82737.09 kPa) Operating Temperature - 40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions
PackageCylinder, MetalSeriesMLHPressure TypeSealed GaugeOperating Pressure8000 PSI (55158.06 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - M14 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure12000 PSI (82737.09 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Category	Sensors, Transducers
SeriesMLHPressure TypeSealed GaugeOperating Pressure8000 PSI (55158.06 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - M14 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure12000 PSI (82737.09 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeSealed GaugeOperating Pressure8000 PSI (55158.06 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - M14 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure12000 PSI (82737.09 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Package	Cylinder, Metal
Operating Pressure 8000 PSI (55158.06 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 5 V ~ 6 V Port Size Male - M14 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style	Series	MLH
Output TypeAnalog VoltageOutput $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $5 \text{ V} \sim 6 \text{ V}$ Port SizeMale - M14 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure $12000 \text{ PSI (82737.09 kPa)}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinder, MetalSupplier Device Package-	Pressure Type	Sealed Gauge
Output $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $5 \text{ V} \sim 6 \text{ V}$ Port SizeMale - M14 x 1.5Port StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure $12000 \text{ PSI (82737.09 kPa)}$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinder, MetalSupplier Device Package-	Operating Pressure	8000 PSI (55158.06 kPa)
Accuracy ±0.25% Voltage - Supply 5 V ~ 6 V Port Size Male - M14 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 12000 PSI (82737.09 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Output Type	Analog Voltage
Voltage - Supply 5 V ~ 6 V Port Size Male - M14 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 12000 PSI (82737.09 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Output	0.5 V ~ 4.5 V
Port Size Male - M14 x 1.5 Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 12000 PSI (82737.09 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Accuracy	±0.25%
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 12000 PSI (82737.09 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Voltage - Supply	5 V ~ 6 V
Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 12000 PSI (82737.09 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Size	Male - M14 x 1.5
Termination Style - 12000 PSI (82737.09 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Style	Threaded
Maximum Pressure12000 PSI (82737.09 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Termination Style	-
Package / Case Cylinder, Metal Supplier Device Package -	Maximum Pressure	12000 PSI (82737.09 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	Cylinder, Metal
Report errors?	Supplier Device Package	-
		Report errors

MLH08KPST03A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MLH08KPST03A Payment Methods



















MLH08KPST03A Shipping Methods













If you have any question about MLH08KPST03A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com