



MLH100PGB06C Information

Heisener.com

Part Number MLH100PGB06C

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description MLH ALL METAL PRESS SENSE -ATF

Package Cylinder, Metal

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MLH100PGB06C Specifications

Manufacturer Part Number MLH100PGB06C Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package Cylinder, Metal Series MLH Pressure Type Vented Gauge Operating Pressure 100 PSI (689.48 kPa) Output Type Analog Voltage Output 1 V ~ 6 V Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package - Report errors?			
CategorySensors, TransducersPackageCylinder, MetalSeriesMLHPressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog VoltageOutput1 V ~ 6 VAccuracy±0.25%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Manufacturer Part Number	MLH100PGB06C	
Package Cylinder, Metal Series MLH Pressure Type Vented Gauge Operating Pressure 100 PSI (689.48 kPa) Output Type Analog Voltage Output 1 V ~ 6 V Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature - 40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions	
PackageCylinder, MetalSeriesMLHPressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog VoltageOutput1 V ~ 6 VAccuracy±0.25%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Category	Sensors, Transducers	
SeriesMLHPressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog VoltageOutput1 V ~ 6 VAccuracy±0.25%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-		Pressure Sensors, Transducers	
Pressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog VoltageOutput1 V ~ 6 VAccuracy±0.25%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Package	Cylinder, Metal	
Operating Pressure Output Type Analog Voltage Output 1 V ~ 6 V Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/8" (3.18mm) NPT Port Style Features Amplified Output, Temperature Compensated Termination Style Aximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package - Cutput Analog Voltage Analog Voltage 40 V Av Automatical Analog Voltage Analog Voltage 40.25% Cylinder, Metal Accuracy Analog Voltage Analog Voltage 40°C ~ 125°C Cylinder, Metal Analog Voltage Analog Voltage Analog Voltage Av Accuracy Accuracy Analog Voltage Accuracy Accuracy Analog Voltage Analog Voltage Av Accuracy Analog Voltage Av Accuracy Accuracy Analog Voltage Accuracy Accuracy Analog Voltage Analog Voltage Av Accuracy Analog Voltage Accuracy Accuracy Accuracy Accuracy Accuracy Accuracy Analog Voltage Accuracy Accurac	Series	MLH	
Output TypeAnalog VoltageOutput1 V ~ 6 VAccuracy±0.25%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/8" (3.18mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination Style-Maximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Pressure Type	Vented Gauge	
Output $1\ V \sim 6\ V$ Accuracy $\pm 0.25\%$ Voltage - Supply $8\ V \sim 30\ V$ Port Size $ \text{Male - 1/8" (3.18mm) NPT} $ Port Style $ \text{Threaded} $ Features $ \text{Amplified Output, Temperature Compensated} $ Termination Style $ $ Maximum Pressure $ 300\ \text{PSI (2068.43 kPa)} $ Operating Temperature $ -40^{\circ}\text{C} \sim 125^{\circ}\text{C} $ Package / Case $ \text{Cylinder, Metal} $ Supplier Device Package $ - $	Operating Pressure	100 PSI (689.48 kPa)	
Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Output Type	Analog Voltage	
Voltage - Supply 8 V ~ 30 V Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Output	1 V ~ 6 V	
Port Size Male - 1/8" (3.18mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Accuracy	±0.25%	
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Voltage - Supply	8 V ~ 30 V	
Features Amplified Output, Temperature Compensated Termination Style - Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Size	Male - 1/8" (3.18mm) NPT	
Termination Style - Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Style	Threaded	
Maximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Features	Amplified Output, Temperature Compensated	
Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Termination Style	-	
Package / Case Cylinder, Metal Supplier Device Package -	Maximum Pressure	300 PSI (2068.43 kPa)	
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C	
	Package / Case	Cylinder, Metal	
Report errors?	Supplier Device Package	-	
			Report errors?

MLH100PGB06C Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MLH100PGB06C Payment Methods





















MLH100PGB06C Shipping Methods













If you have any question about MLH100PGB06C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com