



## **MLH100PGB10A Information**



For Reference Only

Part Number MLH100PGB10A

Manufacturer Honeywell Sensing and Productivity Solutions

**Category** Sensors, Transducers

Pressure Sensors, Transducers

**Description** SENSOR AMP 100PSI .5-4.5VDC OUT

Package Cylinder, Metal

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MLH100PGB10A Specifications**

Manufacturer Part Number       MLH100PGB10A         Manufacturer       Honeywell Sensing and Productivity Solutions         Category       Sensors, Transducers         Package       Cylinder, Metal         Series       MLH         Pressure Type       Vented Gauge         Operating Pressure       100 PSI (689.48 kPa)         Output Type       Analog Voltage         Output       0.5 V ~ 4.5 V         Accuracy       ±0.25%         Voltage - Supply       5 V ~ 6 V         Port Size       Male - 7/16" (11.11mm) UNF         Port Style       Threaded         Features       Amplified Output, Temperature Compensated         Termination Style       Packard Metripak 150         Maximum Pressure       300 PSI (2068.43 kPa)         Operating Temperature       -40°C ~ 125°C         Package / Case       Cylinder, Metal         Supplier Device Package       -	•	
CategorySensors, TransducersPackageCylinder, MetalSeriesMLHPressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard Metripak 150Maximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Manufacturer Part Number	MLH100PGB10A
PackagePressure Sensors, TransducersSeriesMLHPressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard Metripak 150Maximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Manufacturer	Honeywell Sensing and Productivity Solutions
PackageCylinder, MetalSeriesMLHPressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard Metripak 150Maximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Category	Sensors, Transducers
SeriesMLHPressure TypeVented GaugeOperating Pressure100 PSI (689.48 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard Metripak 150Maximum Pressure300 PSI (2068.43 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-		Pressure Sensors, Transducers
Pressure Type Vented Gauge Operating Pressure 100 PSI (689.48 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 5 V ~ 6 V Port Size Male - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Packard Metripak 150 Maximum Pressure 300 PSI (2068.43 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Package	Cylinder, Metal
Operating Pressure  Output Type  Analog Voltage  Output  0.5 V ~ 4.5 V  Accuracy  ±0.25%  Voltage - Supply  5 V ~ 6 V  Port Size  Male - 7/16" (11.11mm) UNF  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style  Packard Metripak 150  Maximum Pressure  300 PSI (2068.43 kPa)  Operating Temperature  -40°C ~ 125°C  Package / Case  Cylinder, Metal  Supplier Device Package  -	Series	MLH
Output TypeAnalog VoltageOutput $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $5 \text{ V} \sim 6 \text{ V}$ Port SizeMale - $7/16$ " (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard Metripak 150Maximum Pressure $300 \text{ PSI } (2068.43 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinder, MetalSupplier Device Package-	Pressure Type	Vented Gauge
Output $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $5 \text{ V} \sim 6 \text{ V}$ Port SizeMale - $7/16$ " (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StylePackard Metripak 150Maximum Pressure $300 \text{ PSI } (2068.43 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinder, MetalSupplier Device Package-	Operating Pressure	100 PSI (689.48 kPa)
Accuracy ±0.25%  Voltage - Supply 5 V ~ 6 V  Port Size Male - 7/16" (11.11mm) UNF  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Packard Metripak 150  Maximum Pressure 300 PSI (2068.43 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Output Type	Analog Voltage
Voltage - Supply  5 V ~ 6 V  Port Size  Male - 7/16" (11.11mm) UNF  Port Style  Threaded  Features  Amplified Output, Temperature Compensated  Termination Style  Packard Metripak 150  Maximum Pressure  300 PSI (2068.43 kPa)  Operating Temperature  -40°C ~ 125°C  Package / Case  Cylinder, Metal  Supplier Device Package	Output	0.5 V ~ 4.5 V
Port Size Male - 7/16" (11.11mm) UNF  Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Packard Metripak 150  Maximum Pressure 300 PSI (2068.43 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Accuracy	±0.25%
Port Style Threaded  Features Amplified Output, Temperature Compensated  Termination Style Packard Metripak 150  Maximum Pressure 300 PSI (2068.43 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Voltage - Supply	5 V ~ 6 V
Features Amplified Output, Temperature Compensated  Termination Style Packard Metripak 150  Maximum Pressure 300 PSI (2068.43 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Port Size	Male - 7/16" (11.11mm) UNF
Termination Style Packard Metripak 150  Maximum Pressure 300 PSI (2068.43 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Port Style	Threaded
Maximum Pressure 300 PSI (2068.43 kPa)  Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Features	Amplified Output, Temperature Compensated
Operating Temperature -40°C ~ 125°C  Package / Case Cylinder, Metal  Supplier Device Package -	Termination Style	Packard Metripak 150
Package / Case Cylinder, Metal Supplier Device Package -	Maximum Pressure	300 PSI (2068.43 kPa)
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	Cylinder, Metal
Report errors?	Supplier Device Package	-
1		Report errors?

#### **MLH100PGB10A Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **MLH100PGB10A Payment Methods**



















### MLH100PGB10A Shipping Methods













If you have any question about MLH100PGB10A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com