



MLH110BST10A Information

Heisener.com

Part Number MLH110BST10A

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description SENSOR SEALED GAUGE 0-110 BAR

Package Cylinder, Metal

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MLH110BST10A Specifications

Manufacturer Part Number MLH10BST10A Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package Cylinder, Metal Series MLH Pressure Type Sealed Gauge Operating Pressure 1595.42 PSI (11000 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 5 V ~ 6 V Port Size Male - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure 3190.83 PSI (22000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package - Report errors?			
CategorySensors, TransducersPackageCylinder, MetalSeriesMLHPressure TypeSealed GaugeOperating Pressure1595.42 PSI (11000 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure3190.83 PSI (22000 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Manufacturer Part Number	MLH110BST10A	
Package Cylinder, Metal Series MLH Pressure Type Sealed Gauge Operating Pressure Operating Pressure Output Type Analog Voltage Output O	Manufacturer	Honeywell Sensing and Productivity Solutions	
PackageCylinder, MetalSeriesMLHPressure TypeSealed GaugeOperating Pressure1595.42 PSI (11000 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure3190.83 PSI (22000 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Category	Sensors, Transducers	
SeriesMLHPressure TypeSealed GaugeOperating Pressure1595.42 PSI (11000 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure3190.83 PSI (22000 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-		Pressure Sensors, Transducers	
Pressure TypeSealed GaugeOperating Pressure1595.42 PSI (11000 kPa)Output TypeAnalog VoltageOutput0.5 V ~ 4.5 VAccuracy±0.25%Voltage - Supply5 V ~ 6 VPort SizeMale - 7/16" (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure3190.83 PSI (22000 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Package	Cylinder, Metal	
Operating Pressure 1595.42 PSI (11000 kPa) Output Type Analog Voltage Output 0.5 V ~ 4.5 V Accuracy ±0.25% Voltage - Supply 5 V ~ 6 V Port Size Male - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure 3190.83 PSI (22000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package	Series	MLH	
Output Type Output Outp	Pressure Type	Sealed Gauge	
Output $0.5 \text{ V} \sim 4.5 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $5 \text{ V} \sim 6 \text{ V}$ Port SizeMale - $7/16$ " (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure $3190.83 \text{ PSI } (22000 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinder, MetalSupplier Device Package-	Operating Pressure	1595.42 PSI (11000 kPa)	
Accuracy $\pm 0.25\%$ Voltage - Supply $5 \text{ V} \sim 6 \text{ V}$ Port SizeMale - $7/16$ " (11.11mm) UNFPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleDeutsch, 3 PinMaximum Pressure $3190.83 \text{ PSI } (22000 \text{ kPa})$ Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinder, MetalSupplier Device Package-	Output Type	Analog Voltage	
Voltage - Supply 5 V ~ 6 V Port Size Male - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure 3190.83 PSI (22000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Output	0.5 V ~ 4.5 V	
Port Size Male - 7/16" (11.11mm) UNF Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure 3190.83 PSI (22000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Accuracy	±0.25%	
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure 3190.83 PSI (22000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Voltage - Supply	5 V ~ 6 V	
Features Amplified Output, Temperature Compensated Termination Style Deutsch, 3 Pin Maximum Pressure 3190.83 PSI (22000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Size	Male - 7/16" (11.11mm) UNF	
Termination Style Deutsch, 3 Pin Maximum Pressure 3190.83 PSI (22000 kPa) Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Style	Threaded	
Maximum Pressure3190.83 PSI (22000 kPa)Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Features	Amplified Output, Temperature Compensated	
Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Termination Style	Deutsch, 3 Pin	
Package / Case Cylinder, Metal Supplier Device Package -	Maximum Pressure	3190.83 PSI (22000 kPa)	
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C	
	Package / Case	Cylinder, Metal	
Report errors?	Supplier Device Package	-	
*		Re	port errors?

MLH110BST10A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MLH110BST10A Payment Methods


































If you have any question about MLH110BST10A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com