



MLH125PGL01C Information



For Reference Only

Part Number MLH125PGL01C

Manufacturer Honeywell Sensing and Productivity Solutions

Category Sensors, Transducers

Pressure Sensors, Transducers

Description MLH ALL METAL PRESS SENSE GAUGE

Package Cylinder, Metal

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MLH125PGL01C Specifications

Manufacturer Part Number MLH125PGL01C Manufacturer Honeywell Sensing and Productivity Solutions Category Sensors, Transducers Package Cylinder, Metal Series MLH Pressure Type Vented Gauge Operating Pressure 125 PSI (861.84 kPa) Output Type Analog Voltage Output 1 V ~ 6 V Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package - Report errors?		
CategorySensors, TransducersPackageCylinder, MetalSeriesMLHPressure TypeVented GaugeOperating Pressure125 PSI (861.84 kPa)Output TypeAnalog VoltageOutput1 V ~ 6 VAccuracy±0.25%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Manufacturer Part Number	MLH125PGL01C
Package Cylinder, Metal Series MLH Pressure Type Vented Gauge Operating Pressure Operating Pressure Output Type Analog Voltage Output 1 V ~ 6 V Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package	Manufacturer	Honeywell Sensing and Productivity Solutions
PackageCylinder, MetalSeriesMLHPressure TypeVented GaugeOperating Pressure125 PSI (861.84 kPa)Output TypeAnalog VoltageOutput1 V ~ 6 VAccuracy±0.25%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Category	Sensors, Transducers
SeriesMLHPressure TypeVented GaugeOperating Pressure125 PSI (861.84 kPa)Output TypeAnalog VoltageOutput1 V ~ 6 VAccuracy±0.25%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeVented GaugeOperating Pressure125 PSI (861.84 kPa)Output TypeAnalog VoltageOutput1 V ~ 6 VAccuracy±0.25%Voltage - Supply8 V ~ 30 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Package	Cylinder, Metal
Operating Pressure Output Type Analog Voltage Output 1 V ~ 6 V Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure Operating Temperature -40°C ~ 125°C Package / Case Supplier Device Package - 125 PSI (861.84 kPa) Analog Voltage Analog Voltage 1 V ~ 6 V Analog Voltage 40.25% 8 V ~ 30 V Accuracy Analog Voltage 40.25% Ed. 25% Accuracy Analog Voltage -40°C ~ 125°C Cylinder, Metal Supplier Device Package	Series	MLH
Output TypeAnalog VoltageOutput $1 \text{ V} \sim 6 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $1/4$ " (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinder, MetalSupplier Device Package-	Pressure Type	Vented Gauge
Output $1 \text{ V} \sim 6 \text{ V}$ Accuracy $\pm 0.25\%$ Voltage - Supply $8 \text{ V} \sim 30 \text{ V}$ Port SizeMale - $1/4$ " (6.35mm) NPTPort StyleThreadedFeaturesAmplified Output, Temperature CompensatedTermination StyleConnectorMaximum Pressure-Operating Temperature $-40^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Package / CaseCylinder, MetalSupplier Device Package-	Operating Pressure	125 PSI (861.84 kPa)
Accuracy ±0.25% Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Output Type	Analog Voltage
Voltage - Supply 8 V ~ 30 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Output	1 V ~ 6 V
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Accuracy	±0.25%
Port Style Threaded Features Amplified Output, Temperature Compensated Termination Style Connector Maximum Pressure - Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Voltage - Supply	8 V ~ 30 V
Features Amplified Output, Temperature Compensated Connector Maximum Pressure Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style Connector Maximum Pressure - 40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Port Style	Threaded
Maximum Pressure-Operating Temperature-40°C ~ 125°CPackage / CaseCylinder, MetalSupplier Device Package-	Features	Amplified Output, Temperature Compensated
Operating Temperature -40°C ~ 125°C Package / Case Cylinder, Metal Supplier Device Package -	Termination Style	Connector
Package / Case Cylinder, Metal Supplier Device Package -	Maximum Pressure	-
Supplier Device Package -	Operating Temperature	-40°C ~ 125°C
	Package / Case	Cylinder, Metal
Report errors?	Supplier Device Package	-
		Report errors?

MLH125PGL01C Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MLH125PGL01C Payment Methods



















MLH125PGL01C Shipping Methods













If you have any question about MLH125PGL01C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com